# THE THREE BIG LIFTS SASHTO – NEW ORLEANS AUGUST 25, 2014







#### Presenters


- □ Brian D. Buckel, PE
  - During Construction LADOTD Chief Construction Engineer
- □ Stephen Spohrer, PE
  - During Construction LTM Deputy Director, Construction



#### The Conceivers

- Special Credit goes to:
- Keith Jacobson, Massman Construction Company, Retired Vice President. Keith followed the strength of his convictions and managed the success of the endeavor.
- John Brestin, PE, formerly HNTB Project Engineer now with Buckland & Taylor Ltd. John designed the temporary works and the lifts.

"Some say that more prayers have been uttered atop the Huey P. Long Bridge than in all the churches of New Orleans and Jefferson Parish combined."



#### The Construction Team













### The Owner Team


















#### The Problem


- The planned obstructions in the River and their impacts on barge and steamship traffic.
- The heavy ship and barge traffic, post-Hurricane
   Katrina.
- Daily Amtrak East-West trains.
- $\square$  24 30 freight trains per day.
- □ 50,000 + ADT
- That this project controlled the opening of the new bridge




STAGE M3 - TASK 12









PLAN - MAXIMUM TRANSVERSE IMBALANCE TRUSS ERECTION AND DECK REMOVAL & CONSTRUCTION

#### (STAGE M3 - TASK 13 SHOWN)

CONCEPTUAL SEQUENCE OF CONSTRUCTION - WIDENING TRUSSES

NOTE (1): REPLACE EXISTING TOP LATERAL GUSSET PLATES WITH REQUIRED ONES FOR WIDENING. NOTE (2): TEMPORARY TOP LATERAL MEMBERS MAY BE REQUIRED TO ACCOMMODATE THE RANGE OF MOVEMENT REQUIRED FOR CONSTRUCTION FOR JOINTS IN THIS REGION. NOTE (3): REPLACE EXISTING BOTTOM LATERAL MEMBERS.

SCALE:1"=200'-0"

FOR NOTES PERTAINING TO THIS SHEET, SEE SHEET NOS. 116 & 117. FOR CONCEPTUAL SEQUENCE OF CONSTRUCTION

- SUMMARY, SEE SHEET NOS. 118-120.
FOR CONCEPTUAL SEQUENCE OF CONSTRUCTION FLOORSYSTEM, SEE SHEET NOS. 128—131.
EXISTING TRUSS NOT SHOWN FOR CLARITY,
ERECTON SHALL BE BALANCED ABOUT THE
LONGITUDINAL AXIS OF THE BRIDGE. MAXIMUM PERMITTED IMBALANCE SHALL BE TWO COMPLETED TRUSS PANEL POINTS.

NEED FOR AND LOCATION OF FALSEWORK MAY BE REVISED AT CONTRACTOR'S OPTION.






HUEY P. LONG BRIDGE WIDENING U.S. 90 MAIN BRIDGE - SUPERSTRUCTURE


Carsons   BEP   Pares   Pare	JEFFERSON		0 10	0-10-000
General   Gene	PARISH	FEDERAL	STATE	
MAEM MEM	. 956 969	SEP A	JULY, 2006	6 of 16
мадиней серейный	CHECKED	DETAILED	DATE	SHEET
6 GENERAL REVISIONS	T		M&M	Br
			1-20-05 GENERAL REVISIONS	REVISION DESCRIPTION
			Market.	-

SHEET 121


STAGE M3 - TASK 14




STAGE M3 - TASK 17




STAGE M3 - TASK 15



STAGE M3 - TASK 18



STAGE M3 - TASK 16



STAGE M3 - TASK 19

#### CONCEPTUAL SEQUENCE OF CONSTRUCTION - WIDENING TRUSSES

NOTE(1): CONTRACTOR TO PROVIDE TEMPORARY LATERAL BRACING DURING ERECTION. NOTE(2): WIND LINK SHALL NOT BE FULLY CONNECTED.

NOTES: FOR NOTES PERTAINING TO THIS SHEET, SEE SHEET NOS. 116 & 117.

A SCISSOR JACK IS SHOWN IN THE LOCATION OF TOP CHORD'S FALSE CHORD MEMBER FOR USE DURING THE WIDENING TRUSS ERECTION TO CONTROL AND ADJUST THE CANTILEVER PORTION OF THE STRUCTURE. THE CONTRACTOR MAY USE A HYDRAULIC JACK WITH SHIMS OR OTHER JACKING MECHANISM THAT WILL SUPPORT THE ERECTION LOADS AND PERMIT THE ADJUSTMENT OF THE WIDENING TRUSS DURING ERECTION.

NEED FOR AND LOCATION OF FALSEWORK MAY BE REVISED AT CONTRACTOR'S OPTION.







MAIN


SHEET 122


JEFFERSON






STAGE M3 - TASK 10







STAGE M3 - TASK 12




STAGE M3 - TASK 13




STAGE M3 - TASK 14




STAGE M3 - TASK 15




STAGE M3 - TASK 16



STAGE M3 - TASK 17



STAGE M3 - TASK 18



STAGE M3 - TASK 19

#### The Solution

- Build three of the four spans in a remote location, barge each to the site, lift each in place in one single 8-hour shutdown of the river, railroad, and highway.
- Stick build the fourth span where it was too shallow and overland.

## The Solution Became the 3 Big Lifts


- □ Each was different:
  - The first lift was the first of the series and in the auxiliary channel.
  - The second lift was in the main channel with greater traffic, all the ship traffic, and higher currents.
  - The third lift was the heaviest.

## Timing is Everything


- All lifts had to occur before or after the Spring rise.
- □ All lifts had to occur before June 1<sup>st</sup> or after
   October 31<sup>st</sup> the hurricane season.
- All lifts had a fallback date two weeks later.


## **HNTB** Animation
















## Big Lift No. 1 - East Anchor Span






## Big Lift No. 2 – Main Span






## Big Lift No. 3 - East Simple Span









## Questions?

