by

AL J. DUNN
ASSISTANT BRIDGE MAINTENANCE ENGINEER

AND

J. G. BIZETTE HIGHWAY TRAINING OFFICER

Research Report No. 61

Research Project No. 71-2M(B) Louisiana HPR 1 (9)

Conducted by
LOUISIANA DEPARTMENT OF HIGHWAYS
Maintenance Section
and
Research and Development Section
In Cooperation with
U. S. Department of Transportation
FEDERAL HIGHWAY ADMINISTRATION

"The opinions, findings and conclusions expressed in this publication are those of the authors and not necessarily those of the Louisiana Department of Highways or the Federal Highway Administration."

January 1972

TABLE OF CONTENTS

SYNOPSIS	V
IMPLEMENTATION	VII
INTRODUCTION	. 1
PURPOSE AND SCOPE	3
METHOD OF PROCEDURE	5
DISCUSSION OR RESULTS	10
CONCLUSIONS	15
RECOMMENDATIONS	16
BIBILIOGRAPHY	17
APPENDIX A - INSPECTION CHECKLIST AND BRIDGE INSPECTION REPORT	A-1
APPENDIX B - SUPPLEMENTAL FIELD DATA	B-1
APPENDIX C - MASTER STRUCTURE FILE	C-1
APPENDIX D - MASTER STRUCTURE FILE CODES	D-1
APPENDIX E - COMPUTER PRINTOUT FORM	E-1
APPENDIX F - BRIDGE NUMBERING SYSTEM	F-1

1

SYNOPSIS

Since the collapse of the Silver Bridge into the Ohio River, the enactment of the Federal Aid Highway Act and a marked increase in national concern for the safety of the traveling public, highway departments throughout the country have directed much more attention to the problem of Bridge Maintenance Inspection.

A comprehensive bridge inspectors training program was developed as a cooperative research project between the states of Florida, Georgia and Louisiana, the Federal Highway Administration and the Link Division of Singer General Precision Inc. of Silver Spring, Maryland.

This report shows generally what three states attempted to do about developing and implementing a bridge inspection program, and more specifically the procedures to be implemented by the State of Louisiana.

Of primary concern was the quality of the inspections being conducted and whether the inspectors themselves were adequately trained to perform this function. It was decided a training program would be needed.

In addition to training personnel, it was decided an inspection system, a filing system, a bridge numbering system and a method of computerizing all structural and inventory and appraisal items to make them available for total or partial recall would be necessary. This has essentially been accomplished, although all information necessary for computerization has

not been obtained, and all bridges have not yet been numbered.

The ground work for the total Bridge Inspection program in Louisiana has been laid, and personnel have been trained to accomplish inspections.

It is felt this is a good program, and complete implementation within the AASHO and Bridge Inspection Training Course guidlines is recommended.

IMPLEMENTATION

The pilot demonstration training program has been validated in Louisiana through the training of 20 Department employees in bridge inspection.

These employees will handle the State's immediate bridge inspection needs. The bridge inspection procedures as outlined in the AASHO manual and as presented in the Bridge Inspectors Training Course are being implemented by the Department as quickly as possible. Inventory information is being accumulated, and the bridges are being numbered by the District bridge inspectors. It is anticipated that eventually the total bridge inspection program will be fully implemented in Louisiana.

INTRODUCTION

The use of modern technology, increased inspections and numerous safety precautions by present day engineers in designing, constructing and maintaining our highway system would seem an almost fool proof way of assuring the safety of the traveling public. Nevertheless, the tragedy of the Silver Bridge's collapse into the Ohio River in 1967 occurred. This collapse prompted the United States Congress to enact the Federal-Aid Highway Act of 1968 which required the Secretary of Transportation to establish national bridge inspection standards and to develop a program to train bridge inspectors.

While some states use graduate engineers for bridge inspection, this is an impossibility in other states. Louisiana is one of the latter states; however, Louisiana recognizes the importance of bridge safety, high inspection standards and properly trained personnel to conduct inspections. Realizing that it would not have enough engineers to assign to bridge inspection, Louisiana sought to find a way to train and utilize the personnel it did have available. Therefore, Louisiana, along with the states of Georgia and Florida, participated in a contract with the Link Division of Singer General Precision Inc. of Silver Spring, Maryland for the purpose of preparing a comprehensive bridge inspection training program. This project was to be conducted as a cooperative research project and funded by 100 percent HPR funds.

The purpose of the bridge program was:

- 1. To serve as a pilot demonstration program, which if successful, would lead to adoption of this course by the Federal Highway Administration as a base line for all training on a national scale.
- To train personnel presently conducting bridge inspections in the three states.

The Bridge Inspection Research study was initiated as a support activity to the development of the training program.

PURPOSE AND SCOPE

It was the intent of the study to provide all the necessary support work connected with the pilot demonstration training course and the subsequently developed inventory, inspection, and data storage and retrieval systems.

The support work consisted of:

- (1) Furnishing photographs which illustrated good, fair, poor and critical bridge conditions in the state. The Technical Policy Committee, comprised of representatives from the three states, the FHWA and Link Division, was to review the photographs for possible inclusion into the training course.
 - Validation of the training methods and recommendations for the revisions ultimately would be a large part of this work.
- (2) Developing an inventory and a structural evaluation form for use by the bridge inspectors. Present forms were inadequate for use because they were not compatible to the AASHO guidelines for bridge inspection. In conjunction with the new forms, an inspection checklist was to be developed to assure that all inspection items were checked by the inspectors.
- (3) Developing or modifying the present data storage and retrieval system.
 This would involve a system of computerizing all inventory and inspection data to make it available for immediate total or partial recall.
 Consideration was also to be given in regard to maintaining a separate bridge file for each structure in addition to the computerized information.

(4) Making recommendations to the Department in regard to whether or not the Singer-Link training methods were adequate for training personnel.

METHOD OF PROCEDURE

It was obvious from the beginning that for the Bridge Inspection Research study to be successful and for a meaningful bridge inspection program to be developed, a joint effort involving several sections within the Department would be necessary. The sections involved were Maintenance, Bridge Design, Traffic and Planning. Data Processing, Research and Development and Project Control.

The Maintenance and Research and Development sections would have the responsibility for:

- (1) Providing photographs as previously discussed.
- (2) Assisting Singer-Link in conducting the training course and validating the training methods.
- (3) Developing the structural evaluation inspection form and the checklist to be used in conjunction with the form.
- (4) Recommending a filing system.

The Maintenance and Bridge Design sections would be responsible for recommending staffing and methods implementation.

The Traffic and Planning and Data Processing sections would have the task of developing the data storage and retrieval systems, the bridge numbering system and the coding for the input forms.

Project Control would supply supplemental field data on maintenance repairs, primarily on the types and estimated costs of repairs.

With the responsibilities delegated to the concerned sections, the job of developing training methods and bridge inspection procedures to be used by Louisiana began.

Training Method Validation and Form Development

Photographs illustrating the bridge conditions in Louisiana were taken. These photos, along with slides depicting similar conditions in Georgia and Florida, were reviewed by the Technical Policy Committee. The slides best illustrating the desired conditions were incorporated into the course. The majority of the slides showing bridge conditions were supplied by Louisiana.

The pilot demonstration training course for Louisiana was conducted at the Bellemont Motor Hotel, Baton Rouge, Louisiana from May 10 through June 4, 1971. The request was made for each of the nine highway Districts to send two employees to attend this class. These were to be the employees whose primary responsibilities were or would be inspecting bridges. In addition, two training specialists were asked to attend the pilot program. It was the Department's intent to use these two specialists to assist in administering this course to additional personnel at a later date.

The training course was 160 hours long, with 120 hours of instruction provided directly by Singer-Link and 40 hours by the State. The method of instruction was audio-visual in nature. The visual aids consisted of slides and Vu-graphs while the audio part was provided by Link instructors, Department representatives and guest speakers. Also included in the 160 hours of training were several field trips.

The trainees were tested prior to the beginning of the training and after the course was completed. The exams consisted of two parts, a written test and practical exercise in actual bridge inspection.

Several different types of inspection forms and checklists were designed, proposed and field tested. In the final analysis it was decided that the checklist would be used as a guide in the field but would not be made a part of the records. (See Appendix A.) The structural evaluation form (Bridge Inspection Report) was revised to include all the inspection items in accordance with the AASHO guidelines. (See page 33 of Appendix A.)

It was decided to set up a bridge file which would have a jacket on each structure that was inspected in the State.

Data Storage and Retrieval and Bridge Coding and Numbering Systems

It was decided by parties concerned that all input data that could possibly pertain to bridges be listed so that there was little possibility that anything would be omitted. The responsibility of obtaining the field data to compile this master file was divided among four sections: Maintenance, Project Control, Bridge Design and Traffic and Planning. Individual forms (Supplemental Field Data) for use by the involved sections except for Traffic and Planning were drawn up. (See Appendix B.) From this data, a master structure file would be made listing all inventory and inspection items that could be obtained. (See Appendix C.)

A coding system for the master structure file was then designed. (See Appendix D, pages D-1 through D-28.) This included special coding instructions for supplemental field data to be furnished by the respective sections. Although this coding guide is different from that suggested in the FHWA coding guide of April 1971, the two systems can be equated to each

other. It should be particularly noted that some of the 84 inventory and appraisal items to be provided have already been accumulated and designated by a plus (+) sign. (See Appendix D, pages D-29 through D-32.) Those items not presently on file that are to be provided by this task force are shown on the bottom of page D-32. Pages D-33 through D-41 show the specific information that the involved sections are to provide for the master structure file.

All of the items on the master structure file will be available for immediate total or partial recall from the computer. An example of the computer printout form is shown in Appendix E.

The next step was to design a bridge numbering system. The bridge number is to be a ten digit number which is composed of the control section (5 digits); the control section log mile (4 digits) and the structure number at the same log mile. This gives a total of ten digits. When an actual number is not in existence in the control section or log mile, a zero (0) will be inserted to insure the ten digit number.

For example: Picture a 4 lane divided highway with 2 service roads. The structure in the right roadway, in the direction of the control, will be bridge number 1. The structure at the same log mile in the left roadway (opposite direction from control) will be bridge number 2. The structure in the right service road will be number 3, and the structure in the left service road will be number 4.

For examples of the bridge numbering system, especially when there is more than one structure at the same log mile, see Appendix F.

The bridge number is to be stenciled in black paint on the inside faces of each bridge rail at the midpoint of the bridge in question. If background color is needed in order for the bridge number to stand out, yellow paint is to be used for background.

Staffing and Implementation

The Department decided that in most cases each District would continue making inspections on its bridges. Each District had sent two men to the pilot training program, and these men would conduct the normal routine bridge inspections.

Inspection of large structures would probably necessitate a task force comprised of personnel from the District and from the Maintenance and Design sections at headquarters level. The District inspectors would give a rating on the component parts of the bridge, and headquarters personnel would give an overall structural rating for the bridge. A staff increase to handle this overall evaluation will probably be necessary.

Pilot Demonstration Training Course

The trainees who participated in the project had wide variance in age, education and experience. These differences in background provided a large amount of class discussion and a beneficial exchange of knowledge. It must be recognized that this training course was designed for three states and was a pilot program. Each state has definite and different training needs. While all needs may not have been satisfied by the course, it is felt that Louisiana has the basic structure of a course, and that with some modification within subject areas it is flexible enough to yield satisfactory results.

The scores on the written part of the final or exit examination were significantly better than on the written entrance examination. The second part of the exit exam, the practical field exercise, also showed the same improvement. However, the practical exercise improvement could possibly be attributed to an increase in time spent inspecting the structure. The time actually spent on the structure varied from 1.5 hours (maximum on entrance examination) to 4.5 hours (maximum on exit examination).

It should be significantly noted that one accomplishment of this training was standardization, not only in terminology but in thinking and evaluation as well. This is borne out by the fact that 17 of the 20 students gave the structure inspected identical ratings on the exit practical examination.

Table 1 shows the entrance and exit examination scores for the trainees (number wrong out of 75).

TABLE 1 *

ENTRANCE EXAM	EXIT EXAM
25	7
29	7
33	8
33	9
34	10
34	10
34	10
35	10
35	11
36	12
37	13
38	13
38	i 4
38	15
38	15
39	16
39	16
39	17
43	21
44	25

* Final Report for Bridge Inspectors Training Program, Table 5, p. 15. (See Bibliography.)

It is not known how much of the improvement noted was attributed to the course itself or to a change in attitudes or motivation. It would be desirable to evaluate inspectors' performance after a period of time. Then an effort should be made to determine which shortcomings in the inspection reports are due to lack of technical knowledge and which can be tied to poor attitudes or lack of motivation. Feedback is very important to the inspector. If he receives no comments, it is logical for him to assume that his reports are good or that they are not being read. Either case will be detrimental toward good attitudes.

It was not the intent here to give a detailed description on the conduct of the pilot training program, but instead to present a concise overview of what the course results were in Louisiana. For a detailed report on the pilot program, refer to the <u>Final Report for Bridge Inspectors Training</u>

Program, DOT-FH-11-7667 of August 9, 1971, by the Link Division of Singer General Precision. Inc.

All revisions recommended by the Technical Policy Committee Chairman as the result of course validation have been made and received by the three involved states and the FHWA.

Structural Inspection Form and Inspector Checklist

After considerable discussion and deliberation over possible formats, the Maintenance Section decided to modify and use the current inspection form for distribution in lieu of the entire checklist. The Research and Development Section's Training Unit devised a checklist patterned after the checklist shown in the Bridge Inspection Training course, and this along with the inspection form is shown in Appendix A. The use of the checklist greatly insures that all inspection items will be checked, and the one page inspection form which consists of subjective ratings by the bridge inspectors gives a concise picture of the condition of the major bridge components. The subjective rating system used is a modification of the AASHO numerical rating system. Again, it is to be noted that the overall structural rating will not be included on this form, but will be determined at the headquaters level.

A separate inventory form for Louisiana was not developed. The inventory information as recommended on page 59 in the AASHO Manual for Maintenance Inspection of Bridges - 1970 will be provided along with additional information afforded by the supplemental field data forms when acquisition of input data is complete.

All the information needed for computerizing bridge inspection inventory and evaluation is not yet complete. Much of the information has been obtained and some of it is already stored in the computer, but much more information will be obtained and stored as time permits, until all items shown in this report are obtained.

Each District is charged with the responsibility for numbering the structures located within that District. All the structures are presently being numbered in accordance with the established numbering system.

Staffing and Implementation Procedures

The responsibility for making recommendations for staffing and implementation has been placed under the jurisdiction of the Chief Maintenance & Operations

Engineer. It is understood that the Department will attempt to implement these new procedures with few, if any, increases in personnel assigned to this function.

It is felt that the District inspections can be handled by personnel presently engaged in this activity.

Filing System

In all probability a file jacket will be made up containing all pertinent information (as built-plans, shop drawings, inspection reports, photographs, etc.) on each structure in the State. The exact method of filing or location

of these files is still being discussed; however, it is felt that a decision will be reached shortly, and a filing system will be implemented.

CONCLUSIONS

- The Bridge Inspection Training course has met its principal objectives. Much knowledge was acquired, and increased accuracy of reporting and substantial standardization were also obtained.
- With certain modifications and updating the course could be totally effective for training bridge inspectors.
- 3. The system of inspecting and reporting bridge conditions, as well as computerizing all inventory and inspection information, should greatly increase efficiency of the total system.
- 4. Greater bridge safety for the traveling public should be provided by new inspection procedures.
- 5. Long range savings of Maintenance funds should occur if inspection findings are used to program timely and efficient repairs.

RECOMMENDATIONS

- All personnel engaged in making bridge maintenance inspections should complete the Bridge Inspection Training course.
- Steps should be taken towards a career development training program for bridge inspectors.
- 3. The AASHO Manual for Maintenance Inspection of Bridges 1970 should be implemented and adhered to.
- 4. The total system of inspecting and reporting, as well as all phases of the bridge inspection program discussed herein, should be implemented.
- 5. The need for periodic recycling of personnel should be evaluated.

BIBLIOGRAPHY

- Bridge Inspector's Training Manual 70. U.S. Department of Transportation, Federal Highway Administration, Bureau of Public Roads. Washington: U.S. Department of Transportation, 1970.
- Final Report for Bridge Inspectors Training Program. DOT-FH-11-7667. Link Division, Singer General Precision, Inc. [Silver Spring, Maryland]: Singer, 1971.
- Manual for Maintenance Inspection of Bridges 1970. Prepared by the Operating Committee on Bridges and Structures, American Association of State Highway Officials. Washington: American Association of State Highway Officials, 1970.
- Recording and Coding Guide for the Structure Inventory and Appraisal of the Nation's Bridges, April 1971. U. S. Department of Transportation, Federal Highway Administration. Washington: U.S. Department of Transportation, 1971.

APPENDIX A

INSPECT	TION CHECKLIST	Page A-1
BRIDGE	INSPECTION REPORT	A-33

NOTE

This inspection checklist is numbered to coincide with the structural inspection report form on the last page of this appendix.

Example:

#59 (Superstructure) - major heading

#17 (Bearings) - subheading

This checklist in no way relates to the rating given a component part of a structure, but is used as a guide for the inspector to follow so that all factors may be considered prior to arriving at a rating.

59. SUPERSTRUCTURE

17. BEARINGS

Elastomeric
Split or torn pads
Buldging
Variable thickness
Abnormal flattening
Metal

Performing design function Rockers free of corrosion, debris Rollers free of corrosion, debris Anchor bolts frozen to bearing Bearing surfaces clean Deflection slots clean Alignment Lubricated bearings functioning properly Bronze sliding plates corroded Rattles under loads Loose or missing nuts in anchor bolts Rocker tilt Horizontal end travel of sliding bearings Binding or damaged Lateral shear keep binding or damaged Corrosion and alignment of cantilever girder hanger connections Corrosion and alignment in pin bearing connections

20. LOWER CHORD

Rusted Needs painting Corroded Damaged

23. FLOORBEAMS

Cracked or spalled
Twisted or swayed
Reinforcing steel exposed
Collision or fire damage
Excessive vibration or deflection
Poor alignment
Cracked or spalled cast-in-place diaphragms
Area around bearings
Corroded end connections or top flanges
Cracks in welds

26. GIRDERS

Corrosion
Deterioration
Reduced cross-sectional area
Signs of slippage
Clean and free from debris
Welds cracked
Misaligned or distorted members
Webs and flanges
Stiffener connections
Excessive deflections or vibrations
Hinges and hangers
Hanger links out-of-plumb
Wind locks
Insides of box girders

29. STRINGERS

Steel

Rust or deterioration
Sagging
Canted
Loose fasteners at connections
Loose clip angles at connections
Cracks in floor beam web
Bottom flange dirty
Cracked welds
Worn or damaged pins
Worn or damaged pin holes
Scaling paint

Timber

Crushed
Decayed
Unsound
Split
Horizontal cracks
Deflecting
Bridging between stringers functioning properly

32. DIAPHRAGMS

Loose or broken connections Rust or other deterioration Buckling Twisting Cracking Spalling

35. LATERAL BRACING

Bolts or rivet heads rusted
Loose or broken connections
Properly adjusted and functioning properly
Adequate under transverse movement and vibration
Rusting, twisting, bending
Members properly adjusted
Cracking in welds, flanges

38. SWAY BRACING

Bolts or rivet heads rusted Loose or broken connections Sash and sway bracing repeated at 10-ft. intervals Adequate under transverse movement and vibration Rusting, twisting, bending

41. VERTICALS

Rusted Corroded Need painting Damaged

44. DIAGONALS

Rusted Corroded Need painting Damaged

47. PORTALS

Rusted Corroded Need painting Collision damage

50. UPPER CHORD

Rusted Corroded Need painting

53. RIVETS AND BOLTS

Loose or insecure Corroded Nuts: rusted corroded loose

56. PAINT

Cracking, chipping, scaling
Rusting, Chalking
"Alligatoring"
Exposed prime coat, metal surface
Repainting needed
"Spot" painting needed
Paint failure on upper chord horizontal surfaces
Painting needed in:
 difficult to paint areas
 areas that retain moisture

59. TRUSSES

```
Steel
     On through trusses, rust causing rapid
          deterioration between adjacent faces of:
               eyebar heads
               pin plates
               other
     On riveted trusses, horizontal surfaces and
          connections of lower chord members corroding
     Expanding rust on inside surfaces of laminated or overlapping
          plates causing deformation
     Members:
          buckled
          torn
          misaligned
     Local buckling, indicating overstress of a compression
          member
     Joints:
          looseness
          slippage
     Pins:
          scoured
          worn
     In place:
          spacers
          nuts
          retaining caps
          kevs
     Metal clashes under live loads
     Stresses evenly divided in sections of tension members
     Counter members properly adjusted
     Abnormal cracking in looped rod tension members
     Cracks in eyes of eyebar member
     Spacers on pins holding in proper position:
          eyebars
          looped rods
     Physical condition of threaded members
```

```
Timber
     Weathering
     Checking
     Splitting
     Decay
     Crushing:
          ends of compression chord
          diagonal members
     Splices decayed
     Bolts and connections tight
     Decay:
          at contact surfaces of joints
          around holes where bolts are fitted
          end panel joints
     Bridge seat:
          dirt accumulation
          debris
     Adequate protection to structural members by:
          roof
          slides
     Is truss misaligned
     Fire hazards:
          brush or drift
          combustible materials
          vehicle parking
          fires built
```

18. Welds

Cracked Broken

- 21. COLLISION DAMAGE
- 24. DEFLECTION UNDER LOAD
- 27. VIBRATION UNDER LOAD
- 30. ALIGNMENT OF MEMBERS
- 33. CLEANLINESS

36. UTILITIES

Pipe, ducts, etc. leaking, broken, cracked coverings deteriorating Corrosion, damage, loose connections General lack of rigidity Mounts rattle under traffic need padding Leaking in: annular space between pipe blocked up area where utilities pass through abutments Leaky water or sewer pipe: above decks on top of beams Mutually hazardous transmittants sufficiently isolated from each other Adequate roadway clearances Obstructing waterway area Hindering drift removal Damage to encasements of pipes carrying fluids under pressure Leaks in: vents, drains

Shut-off valves on pipelines carrying
hazardous pressurized fluids adequately
supported
Power cables:
wearing
deteriorating shielding, insulation
Impairing structural integrity
Interfering with bridge maintenance operations
Cracking in support members due to:
vibrations
expansion movements
Adverse aesthetic effect on bridge

MOVABLE SPANS

42. WEDGES

Loose knee pins
Excessive play
Function properly on:
 closing
 releasing

45. OPERATING MACHINERY

Alignment of: gears, locks other interlocking mechanisms Movable parts adequately lubricated Lubrication schedule: frequency sufficient Pin locks function properly on: closing releasing Cracks in gears Shafts: twisting straining play within bearings Keyways: loose on shafts and gears loose on keys Cracking in: braces bearings housings

Cracks in concrete at:

bearing plate attachments

brace attachments

Bolt tight

Brake devices functioning properly

Stops: used, needed Debris on machinery Rust on machinery

Motors and Engines:

If belt drive: wear, slippage, belts need replacing If friction drive: wear, uneven bearing areas

If direct drive: brackings and bearings tight

If liquid coupling: proper quantity of fluid being used leaks

Flexible cable to motor in good condition

Auxiliary Power

Condition good and reliable

On double-leaf bascules: both sides have auxiliary power systems

On hand-cranked systems:

standing platform free of grease, debris can a portable generator-powered device replace manpower

48. MACHINERY GREASING

Visual signs of wear Frequency of greasing Cable greasing

51. ELECTRICAL SYSTEM

Excess play
Sparks
Proper functioning of:
 wiring, motors, conducts, lights
Worn or broken lines
Hazardous conditions
Rusty or mismatched members
Controller outdated
Parts need replacing
Electrical interlock working
Overheating of Span Speed control resistor banks

54. CONTROL HOUSE AND PANEL

Changes from normal operation Structure: cracking windproof, insulated Bulletins posted: Coast Guard Corps of Engineers local Hazardous operating conditions Accumulating combustible material Panels: doors secured located in proper relation to: roadway waterway if control box with no tender: security system functioning properly tender has any complaints about panel tender's log up-to-date tender has good view of approaching: boats vehicles

57. NAVIGATION SIGNAL DEVICES

Working properly
Sufficient amount of alternate warning devices available:
bull horns
lanterns
flasher lights
flags

ADD: COUNTERWEIGHTS AND ATTACHMENTS

Sound
Properly affixed to bridge
Steel members corroded
Concrete:
 rust stained
 cracked, spalled
Debris, animals
Insect nests, birds nest
Deteriorated:
 links, slides
 housings, storage area bridge balanced

Extra weight blocks available Pain periodically removed Properly drained

ADD: SUBMARINE CABLES

Clamps and securing clips satisfactory

19. DECK

```
Concrete
     Scaling, spalling
     Reflection cracking
     Potholes
     Hollow areas
     Surface cracking
     Underside cracking
     Wet concrete leaching
     Reinforcing steel:
          exposed
          rusting
     Surface:
          worn
          polished
     Joints:
          grout in good condition
          spalled
     Rod nuts:
          loose
          tiaht
          rusted
     Curb alignment good
Steel
     Corrosion
     Cracked welds
     Broken welds, clips
     Deck securely fastened
     Loss of section due to:
                                rust, wear
     Deck slippery when wet
     Effect of utilities bad
     If an open-grating deck:
          cracked welds
          slippery when wet
Timber
     Planks:
           loose
          broken
          worn
     Fasteners:
           loose
          missing
     Decay
     Asphalt overlay:
          potholes
          cracks
     Members under traffic:
           looseness
          excessive deflection
     Deck slippery
```

```
Deck draining properly
Effect of utilities bad
Felloe guards:
    properly aligned
    in good condition
    bolted in place
Ballast:
    potholes
    rust
Tread plates:
    loose
    slick
Striping needed
```

22. CURBS

```
Concrete
     cracking
     spalling
     deteriorating
Timber:
     splitting
     warping
     decaying
Projecting onto roadway, shoulders
Loss of curb height:
     due to build-up of deck surface
Timber wheel guards or scupper blocks:
     split
     checked
     decayed
Bolted securely in place
Paint in good condition
```

25. SIDEWALKS

Cracking
Spalling
Deterioration
Differential movement at joints
Corrosion
Connections secure
Timber sound
Floor planks adequately supported

Planks: missing cracking decaying warping nails protruding Sidewalks slippery, rough Drainage adequate Structural intergrity of brackets

28. BRIDGE RAILS

Collision damage Weakening from deterioration In concrete or rebars: cracking corrosion disintegration In steel or aluminum: loose posts or rails rusting or deteriorating Post connections to deck: in good condition Timber: decaying loose connections missing rails damaged rails Vertical and horizontal alignment: show settlement in substructure bearing deficiencies Handrail joints: onen functioning properly Handrails: height adequate secure free of slivers free of hazardous projections

Rust stains on concrete around steel posts

Barrier railings:

extend beyond parapet end
extend beyond end of bridge railing
anchored to inside face
damaged
misaligned
cracked
deteriorated
corroded

Parapet ends:
unprotected
need installation of flared, tapered railing

Anchor bolts and nuts tight

34. EXPANSION JOINTS

Freedom of movement Proper clearance Proper vertical alignment Sufficient room for expansion Closed Widely opened Seals: pulling away from joint edges abrasive shriveling deteriorating Stains, leaking Voids, laminations Any improperly sealed joints need: cleaning resealing Free of: stones debris Steel finger type joints: loose anchorages cracking or breaking of welds jammed by resurfacing Sliding plate joints: loose anchorages cracking or breaking of welds

31. FIXED JOINTS

Any movement
Proper clearance
Proper vertical alignment
Stains, signs of leaking
Free of stones, debris
Any clogged by resurfacing

37. JOINT LEAKAGE

40. DRAINAGE

Deck or deck inlets:
 clogged
 inadequate openings

Any water stains on:
 beams
 piers
 abutments

Drain outlets discharging water
 where detrimental to other members

Pipes damaged by:
 freezing
 corrosion
 collision

Pipes clogged

Any deck sand or soil accumulation

43. PROFILE ELEVATION

Visible settlement

46. PARAPET

Spalled Cracked Damaged

49. LIGHT STANDARDS

```
Poles:
     dented, scraped
     cracked, inclined
     otherwise damaged
Aluminum standards cracking in:
     mast arms
     cast fittings
     base
     cast elements
Steel rusted
Concrete:
     cracked
     spalled
Exposed wiring insulation:
     faulty
     worn
     damaged
Evidence of:
     bad wiring practices
     bunches of excess wires
     poor wire splices
     inadequate securing of ground lines
     loose wires
Junction boxes:
     poor wire splices
     loose connections
     excessive moisture
     outlet or switch box covers out of place
Conduits:
     rustedmissing sections
Conduit braces and boxes properly secured
Hanging braces and boxes properly secured
Hanging fishing lines or moss
Missing lamps
Sign lighting adequate
```

60. SUBSTRUCTURE

63. ABUTMENTS

Scour Erosion Movement Settlement Drains and weepholes: clear functioning properly Bearing seats: cracked spalled Deteriorating concrete Backwalls: cracked weathered spalled leaking

66. BACKWALL

Settlement Tilting Spalling Cracking Rotting Damaged

69. WINGWALL

Settlement Tilting Spalling Cracking

72. BULKHEAD

Rotting Broken timbers

75. CAPS

78. BENT PILES

```
Concrete
     Erosion
     Undermining of foundation by scour
     Exposed piles
     Evidence of tilt
     Settlement
     Disintegration:
          in splash zone
          wherever exposed to roadway drainage
          at water line
          at ground line
     Pier columns cracked
     Pier caps cracked
     Bearing seats:
          cracked
          spalled
     Stone masonry piers:
          cracked
          water or vegetation in cracks
     Stones:
          spalled
          split
          loose
          missing
     Corroded steel piers or bents at:
          joints
          splices
```

```
Grout pads or pedestals:
          cracked
          spalled
          deteriorated
     Steel piles in splash zone or below surface:
          deteriorated
    Any significant changes in clearance, indicating
          pier movement
     Structural damage to:
          piers
          bents
     Where steel cap girder and continuous
          longitudinal beams are framed
          together, any cracked
               top flanges
               welds
               webs
     Unusual movement in bent
          members under heavy loads
     Movement of freely rotating rocker bents
          restrained by:
               severe corrosion
               foreign particles
               other debris
     Earth or rock fills, piled against piers
Steel
     Rust:
          at ground level
          in splash zone (2' above high tide or mean water level)
          in submerged part
     Debris around bases
     Steel caps rotating due to eccentric
          connections
     In bracing:
          broken connections
          loose rivets
          loose bolts
     Condition of web stiffeners
Timber
     Decay in:
          piles
          caps
          bracing
     Decay beginning at:
          ground line
          water line
          joints and splices
     Loose bolts in:
          splices
          connections
```

```
Fungi
      Marine borers
      Shipworms
      Footing piles exposed
      Damage to:
           wood
           bolt holes
           daps
           other connections
BENTS AND 64. PIERS
 Erosion or undermining of foundation by scour
 Evidence of:
      tilt
      settlement
 Disintegration of concrete:
      splash zone
      water line
      ground line
      where exposed to roadway drainage
 Pier columns cracked
 Pier caps cracked
 Bearing seats:
      cracked
      spalled
 Corroded steel piers or bents at:
      joints
      splices
 Grout pads or pedestals:
      cracked
      spalled
      deteriorated
 Steel piles in splash zone or below surface:
      rusted
      deteriorated
 Pier movement, indicated by changes in clearance
 Structural damage
 Where steel cap girder and continuous
       longitudinal beams are framed together:
            cracked top flanges
            cracked welds
            cracked webs
 Unusual movement under heavy loads
 Where freely rotating rocker bents, movement
      restrained by:
            severe corrosion
            foreign particles
            other debris
```

9.

Earth or rock fills piled against piers

67. COLUMNS

Steel

rusted, corroded damaged by collision

Concrete

spalled c**rac**ked

damaged by collision

70. PEDESTAL

Undermining and erosion Cracked Broken

73. FOOTINGS

Settlement Tilting Undermining by erosion Cracking

76. FOUNDATION PILES

Exposed

79. BRACING

10. SETTLEMENT

65. CONCRETE CRACKS AND SPALLS

- 68. STEEL CORROSION
- 71. TIMBER DECAY
- 74. COLLISION DAMAGE
- 77. PAINT
- 80. CLEANLINESS

72. APPROACH

15. CONSTRUCTION JOINT

```
Vertical displacment at joint of bridge backwall
Joint seal:
    damaged missing
Clogged
Other transverse joints:
    closed clogged
```

18. PAVEMENT

Uneven
Rough
Cracked
Potholes
Approach:
 too wide for bridge
 to narrow

21. RELIEF JOINT

Is 4" opening correct Clogged

24. APPROACH SLAB

Under or alongside of slab:
 erosion
 voids
Settlement
Tilting
Spalling
Cracking

27. GUARDRAIL

Good condition Collision damage Constructed according to standard plans

30. ALIGNMENT

33. RETAINING WALL

Soil under embankment settling
Timber cribs:
 decayed
 termite ridden
Concrete cribs:
 chipped
 spalled
Locking keys:
 damaged
 missing
Flanges:
 damaged
 missing

36. SHOULDER

Proper width Good condition At proper grade

39. EMBANKMENT

Slopes: adequate maintained

42. DRAINAGE

Adequate Maintained Erosion

61. WATERWAY

GENERAL

Water marks on: painted structure trees Existing bank and shore: adequate in good condition Levee erosion cuased by: improper location skew of bridge piers or abutments Existing protection need to be: added to revised High backwater caused by: high fills inadequate or debris-jammed culverts Wave action affecting: bridge approaches Problem areas around: bridge approaches

16. REVETMENT

Undermining

19. RIPRAP

Undermining

22. SPUR DYKE

Erosion Functioning properly

25. EMBANKMENT EROSION

28. CHANNEL SCOUR

Scour tendencies indentified by taking: channel profiles channel soundings Degradation

31. CHANNEL CHANGE

Impairing or decreasing effectiveness of present protection

34. VEGETATION

37. DRIFT

Debris:

under deck on bridge seats along banks upstream around bridge other signs of structural failures
loose cables
broken cables
missing walers
missing blocks
missing bolts
Protective treatment
need patching
need replacing
Catwalks in good condition

43. ADEQUACY OF OPENING

TRAFFIC SERVICES

17. SIGNS

Additional ones needed If built before 1940: is weight limit posted Clearances meet 13' 6" minimum standard If sub-standard: "Low Clearance" sign If bridge is narrower than approach: "Narrow Bridge" sign If a narrow underpass: traffic effectively warned Speed and traffic markers appropriate If movable bridge: warning signs for: draw spans submarine cables interconnected traffic signals drawbridge gates warning signs in advance Side-mounted signs: 30' from roadway edge located behind barrier or guardrail affixed to a breakaway installation Hazardous sign supports

Caution signs:
 in good condition
 vandalized
 meet minimum size requirement
 reflectorization or painting adequate
 for night visibility
 obscured by heavy growth
 need to be relocated

Supports:
 bent
 twisted
 otherwise damaged

20. STRIPING

Adequate for night visibility Needs to be re-done

- 23. HAZARD MARKER
- 26. AERIAL SIGNAL
- 29. WARNING DEVICES
- 32. CLEARANCE SIGN
- 38. LEGIBILITY

44. NAVIGATION LIGHTS

```
All present
Properly located
If a fixed bridge:
     green light suspended from
          superstructure over channel centerline
     red lights:
          marking channel edges
          on piers, fenders
If a movable span:
     lighting meets requirements of:
          Section 68, Coast Guard Pamphlet CG 204
Lighting devices:
     rusted
     broken lenses
     missing lenses
If a movable span:
     lighting meets requirements of:
          Section 68, Coast Guard Pamphlet CG 204
Lighting devices:
     rusted
     broken lenses
Functioning properly
Loose or corroded:
     wiring
     conduits
     securing devices
Aerial obstruction lights:
     functioning properly
     meet requirements of that brige
```

PAGE ___

STATE OF LOUISIANA DEPARTMENT OF HIGHWAYS

FURM 30%. REV. 11/71

TYPE INSPECTION

BRIDGE	INSPECTION	REPORT

	BRIDGE INSPECTION REPORT								
٠,	IN DEPTH SUPPLEMENTAL								
BRODGE NAME OR FEATORE									
CONTROL SECTION LOGMI 21.D.NO. 3 RECALL NO. 8 9 FIELD BOOK NO.									
	— —	77.7.7.5	Γ			1			
L.									
	BRIDGE TYPE								
£> A	PARISH BRIDGE TYPE								
en	HDGE LE	NGTH		ROWY, WIDTH			SURFACE TYPE	ADT	
311	OVERALL 15 OVERALL 16								
59	SUPER	STRUCTURE		#ATING	58 C	ECK RATING	REMARKS		
	17	BEARINGS	18	WELDS	19	DECK			
	20	LOWER CHORD	21	COLLISION DAMAGE	22	CURBS			
	23	FLOOR BEAMS	24	DEFLECTION	25	SIDEWALK			
	26.	GIRDERS	27	UNDER LOAD VIBRATION	28	BRIDGE RAIL			
	29	STRINGERS	30	UNDER LOAD ALIGNMENT OF	31	FIXED JOINT			
		ł	<u> </u>	MEMBERS	31	- FIXED JOINT			
	32	DIAPHRAMS	33	CLEANLINESS	34	EXPANSION JOINT			
	35	LATERAL BRACING	36	UTILITIES	37	JOINT LEAKAGE			
	38	SWAY BRACING	MOVAB	LE SPANS PYERAL CO	40	DRAINAGE			
	, e	SWAT BRACING	1 1		40	DRAINAGE			
	41	VERTICALS	42	WEDGES OPERATING	43	PROFILE ELEV.			
	44	DIAGONALS	45	MACHINERY	46	PARAPET			
	47	PORTALS	48	MACHINERY GREASING ELECTRICAL	49	LIGHT STANDARDS			
	50	UPPER CHORD	51	SYSTEM	52				
	53	RIVETS & BOLTS	54	CONTROL PANEL	55				
	56	PAINT	57	NAVIGATION	58	7			
	59		60	SIGNAL DEVICES	61	-			
	·	<u> </u>	1 00 1	1		RALL 62			
60	SUBSTI	RUCTURE			RAT	ING			
	63	ABUTMENTS	64	PIERS	65	CONC. CRACKS			
	66	BACKWALL	67	COLUMNS	68	STEEL CORROSION			
	69	WINGWALL	70	PEDESTAL	71	TIMBER DECAY			
	72	BULKHEAD	73	FOOTINGS	74	COLLISION			
		1		FOUNDATION	\vdash	- DAMAGE			
	75	CAPS	76	PILES	77	- FAIN!			
!	78	BENT PILES	79	BRACING	80	CLEANLINESS		· · · · · · · · · · · · · · · · · · ·	
كا	3	BENTS	10	SETTLEMENT	11				
72	APPRO	ACH OVERALL 12	61 WAT	ERWAY OVERALL 13	TR.	SER. OVERALL 14	<u></u>		
	T T	T	† 	T	+	SPEED LIMIT			
	15	CONST. JOINT	16	REVETMENT	17	SIGN			
	18	PAVEMENT	19	RIPRAP	20	STRIPING			
	21	RELIEF JOINT	22	SPUR DYKE	23	HAZARD MARKER			
	24	APPROACH SLAB	25	EMBANKMENT EROSION	26	AERIAL SIGNAL			
	27	GUARDRAIL	28	CHANNEL SCOUR	29	WARNING DEVICES			
	30	ALIGNMENT	31	CHANNEL CHANGE	32	CLEARANCE SIGN			
	33	RETAINING WALL		1		-	 		
	 	1	34	VEGETATION	35	BARRIERS & GATES	 		
	-5	SHOULDER	37	DRIFT	38	LEGIBILITY			
	39	EMBANKMENT	40	FENDER SYSTEM ADEQUACY OF	41	VISIBILITY			
	42	DRAINAGE	43	SPENING	44	NAVIGATION LIGHTS			
	45		46		47				
CR:	CRITICAL 9-1-2 POOR 3-4-5 FAIR 6-7 GOOD 8-9 RECOMMENDED 48 51								
						52 55	XT INSPECTION 56	OVE DA 1 57	
TOTAL STRUCTURAL STRUCTURAL									
						MO. YR.	· - 	RATING	
APPROVED BY					DATE	and the second s	POSTED 58 59	60 61	
						LOAD	DESIGN LOAD		
						SC	CHEDULE MAINT, REPA	WR5	
	USE -	WHEN ITEM NOT APPL	CABLE			L	IMMEDIATELY		
	ROUTINE								


APPENDIX B

SUPPLEMENTAL FIELD DATA


NOTE


In addition to the supplemental data provided by these forms the inspection data from the last bridge inspection report (Appendix A page 33) is also furnished for compilation into Master Structure File (Appendix C).

POPLICATION SUPPLEMENTAL DATA FOR NUMBER TOUR TOUR STAND TOUR SUPPLEMENT OF STAND SUPPLEMENT OF SUPP	+					+
APPLICATION SUPPLEMENTAL DATA FOR CODED BY PROJECT CONTROL RANGER TOURS BLAUS TOURS TOUR	,					
APPLICATION SUPPLEMENTAL DATA FOR CODED BY PROJECT CONTROL RANGER TOURS BLAUS TOURS TOUR	`			, , ,	'	
APPLICATION SUPPLEMENTAL DATA FOR SUPPLEMENTAL DATA FOR CODED BY PROJECT CONTROL				MAJOR CONSTR	AS BUILT	
SUPPLEMENTAL DATA FOR SUPPLEMENTAL DATA FOR SUPPLEMENTAL DATA FOR	ew.		NUMBER URS	JCTION		
LOBM ECS-D32			NUMBER URS	JCTION		
	EM .	ТЭЗГОЯЧ	R R	7000 T234	SAM NO	APPLICATIO VB 03000
		ТЭЗГОЯЧ	R R	7000 T234	SAM NO	APPLICATIO VB 03000



COUSIANA DEPT. OF HIGHWAYS






APPENDIX C MASTER STRUCTURE FILE


O X D H		DEC CH*		m e e e e
64 X	4	-0 ×		ord Name
	LATITUDE	3 4	I. D. NUMBER	1 4 4
70	LONGITUDE	- 5 -		STRUCT, I
======================================		7 8 9	CONTROL	JCT, MASTER
- \frac{1}{25} - \frac{6}{7}	A. D. T.	10 1 1 2 3 4	LOG	70
<u>8 .</u> <u>9 .</u>	NO. OF TRAF. LANES NO. OF SAFETY LANES	15	MILE	LOUISIANA
80 -1 -2	NO. OF LANES CROSSED DIVIDED - TWIN		BRIDGE I.D. STR. COUNT BRIDGE RECORD	FLAGS
3 <u>4</u> <u>85</u>	STRUCTURE CODE PHY. VULNERABILITY	7 8 9 20 1 2 3 4 25	MAJOR BRIDGE UNDER 20° SECTION	DEPAI
	SUPERSTRUCTURE PIERS ABUTMENT PILES	$\begin{bmatrix} \frac{2}{3} \\ \frac{3}{4} \end{bmatrix}$	NUMBER	DEPARTMENT
9 90 1	FOUNDATION P	25 6 -7	BRIOGE LETTER	9 Q
234	RIDING SURFACE SURFACE THICKNESS	27 8 9 9 30	SECTION MILE POST	PEFENSE
- <u>95</u> - - 6 - - 7	OPERATION PROTECTION AVERAGE	DESCR 1 2 2 3	SECTION	1 1
$\begin{bmatrix} \frac{8}{9} \\ \frac{100}{100} \end{bmatrix}$	AVERAGE MONTHLY OPENINGS	2 3 4 35 6	LENGTH	RECORD
$\begin{bmatrix} \frac{1}{2} \\ \frac{3}{3} \end{bmatrix}$	SECTION	8 9	STATE ROUTE NUMBÉR	APPLI
105 6	TOTAL LENGTH	1 2		APPLICATION
7 8 -9	LENGTH	2 3 4 45 6	FEDERAL ROUTE NUMBER	SHEET
$\frac{\frac{110}{1}}{\frac{2}{2}}$	OF MAX. SPAN	-6 -7 -8 -9	DISTRICT	TUR
115 115	NO. OF SPANS	50	STATE CITY NUMBER	LOCATION S
6	SECTION STRUCTURE	, 2 3 4 55 6 7 8 9 60 1 2	NAT. GEOG. CITY CODE	
120 1	STRUCTURE CODE NO. OF SPANS	55 6 7	PLACE CLASS STATE SYS.	1
1_4	D MAX. D SPAN	8 9 60	FED. SYS. U. S. NO. SYS. MAINT. BY	Pose 1
125 63 127	LENGTH SECTION	1 2 61 X	TOLL - FREE SHARED COST	0,01
				· , ,

	OM CH ▼			DEC X			7) 92
	., ~				311/00/01/01	11	ਕ ਨੂੰ ਫ
	192 X -3 X -4 X	NO.		128 🗶	CODE NO.	SECOND	Name
	1 ×	SPANS		120	OF SPANS		<u>'</u> [
	195 0	MAX. SPAN		1 ×	MAX.	EXTRA	T T
	1 2	LENGTH		3 b	SPAN LENGTH		STRUCT
	_8 X	DESIGN LOAD		135 X	SECTION		1
	200	- OPERATING	CA	6	STRUCTURE CODE	THIRD	AS
	1 -1	RATING	CAPACITY	7 8	NO.		MASTER
	3	INVENTORY		9 140 🗙	OF SPANS	EXTRA	
	205	RATING	DATA	1 8	MAX.	P	5
	-6-	POSTED LOAD LIMIT		3 0	SPAN LENGTH		LOUISIANA
	- <u>7</u>	POSTED	1		SECTION		AIS
	9	SPEED LIMIT	}	145	STRUCTURE CODE	50	NA
	210	DESIGN A.D.T.		4 X 145 6 7 8 9 X 150 0	NO.	FOURTH	D.
	2 -	STRUCTURE FLARED	-	-8 -9 X	OF SPANS	EXTRA	DEPARTMENT
	4	CURB/CURB	1	150 0	MAX.	\$	꾸
	$\frac{215}{6} =$	SHOU/SHOU RIGHT		=======================================	L FNGTH		M ≤
	1 [CURB/CURB SHOU/SHOU LEFT	-	_3 X	SECTION	17	_ Z
	8 -	SHOU/SHOU S		155	STRUCTURE CODE	HIAIA	On On
	220	RAIL/RAIL		<u>6</u> _7_	NO.		
	1-1-	RIGHT		8_	SPANS	EXTRA	GH/
Į.	3 -	RAIL/RAIL		9 7			HIGHWAYS
· ·	225	LEFT	_	160 3	LENGTH		Į.
	-6-	TYPE S		$\frac{2}{3}$	SECTION STRUCTURE	- 2	RECOR
	8	MATERIAL E		4	CODE	HTXIS	COR
1	230	NUMBER O		165	NO. OF	EXTRA	
		WIDTH SIDE OF STR.		}	SPANS	3	D LAYOUT
	2 -			, <u>8</u> .	MAX. SPAN) ATI
	4	OUT TO OUT STRUCTURE	EAR!	170	LENGTH	4	
	235	WIDTH	CLEARANCES		STRUCTURE	- SE	SHEET
	7 8	WIDTH @	-	3 - 4 -	CODE I	国	CC TET
	9	OVERHEAD	1	175	F OF	SEVENTH EXTRA	G.
	240	TOTAL	1	6 >	JEMN3	그림	S.
	2	SHOULDER WIDTH		$\frac{-7}{8}$	SPAN		
	3-	MEDIAN TYPE MEDIAN	-		S- LENGTH	+-	
	245	WIDTH		! _	STRUCTURE	- E	
	6 7	CENTERLINE		2 	CODE NO.	IGHTH EXTRA	
	8_			4	OF	EX	
	<u>9</u> _	RIGHT		185 X	.	18	Page Cote
	1-1	RIGHT	<u> </u>		SPAN		re 2
	1,-3			8_ X	SECTION	z	C.
	255 X	LEFT CURB		190 >	STRUCTURE CODE	N I	0
	1 = 22 = 5	- COND (1	∵ ⊤وا		اد	j



B W C T T T T T T T T T T T T T T T T T T	ת
B W W W	Record Name
448 X CLEANLINESS 384 X 5th 9 UTILITIES 385	2 03
[1450 OVERALL RATING _ O _ [
WEDGES MACHINERY MACHINERY MACHINERY MACHINERY MINUSER MINUSER	STRUCT.
GREASING 9 CONSTRUCTED	Ĉ
455 CONTROL PANEL & 1	
*6 SIGNAL DEVICES & 2	MASTER
7 OVERALL RATING 3	Ä
18 DECK 4 TYPE PLANS 19 CURBS 395 AVAILABLE	2 0
460 SIDEWALKS 6 AS BUILT?	_
FIXED JOINT 8 FILED	0
3 EXPANSION JOINT & 9	LOUISIANA
4 JOINT LEAKAGE 400 EXTRA 465 DRAINAGE 1 SPACE	AN
6 PROFILE ELEV. 2	I I
7 PARAPET 8 LIGHT STANDARDS 9 OVERALL RATING 4 405	DEI
	DEPARTMENT
ABUTMENTS 6 COST BACKWALL 7 OF	2T N
2 WINGWALL STRUCTURE	V EL Z
BACKWALL The structure of the structure	
14/5 DEM 11653	유
6 - BENTS 2 - STRESS ANAL. DATA PIERS WHERE	픚
)H
8 - COLUMNS STREET STREET	HIGHWAYS
1 FOUND. PILES S Z COMPLETION	f f
1 FOUND. PILES S Z COMPLETION 2 BRACING 8 DATE	RECOR
1 4 FCRACKS & SPALLS! 420 F OF	S S S
485 STEEL CORROSION 1 MAJOR RECONSTRUCTION	1 —
7 COLL. DAMAGE 3	APPLICATION
8 - PAINT UATE OF	CAT
490 OVERALL RATING 6 INVENTORY	ion I
490 OVERALL RATING 6 INVENTORY CONST. JOINT 7 PAVEMENT 8 RELIEF JOINT 9 BEARINGS' APPROACH SLAB 5 LOWER CHORD	SHEE
3 RELIEF JOINT 3 BEARINGS' 4 PAPPROACH SLAB 3 430 LOWER CHORD	RUG
4 - APPROACH SLAB TO LOWER CHORD 495 - GUARDRAIL ALICAMENT THE STATE OF THE STAT	HEET STRUCTURES
ALIGNOCAL	RE
7 RETAINING WALL 3 STRINGERS 8 SHOULDER 4 DIAPHRAGMS	S
9 EMBANKMENT 435 LATERAL BRACING M -	
500 PRATNAGE / SWAY BRACING SWAY	
1 - Z - Nett victor A - O'MOUNTES	·
A SPUR DIKE	
505 EMBANK, ERROS, EN 1 RIVETS & BOLTS	
6 CHANNEL SCOUR 2 PAINT 7 CHANNEL CHANGE 2 3 WELDS	() 1) () () () () () () () ()
8 VEGETATION 4 COLLISION DAMAGE	L.
19 DRIFT 445 DEFLECTION 510 FENDER SYSTEM 6 VIBRATION	(·_ σ·
SIL X ADEQ. OPENING 447 X ALIGNMENT	

521 58 59 60 60	7 8 9 10 1 2 3 4 5 6 7 8 9 10 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8	TYPE SERVICE TYPE OF WORK LENGTH OF IMPROVEMENT PROPOSED PROPOSED ROADWAY WIDTH PROPOSED NC. OF LANES NEW DESIGN A.D.T. ESTIMATE YEAR OF A.D.T. ESTIMATE YEAR OF ADJ. IMPROVEMENT TYPE ADJ. IMPROV. COST OF PROPOSED IMPROVEMENT TYPE ADJ. IMPROV. COST OF PROPOSED IMPROVEMENT TYPE ADJ. IMPROV. TYPE ADJ. IMPROV. TYPE ADJ. IMPROV. TYPE DATE TYPE TYPE TYPE	PROPOSED IMPROVEMENTS	512 X 512 X 513 X 515 6 7 8 9 525 6 7 8 9 530 1 2 3 4 545 6 7 8 9 540 1 2 3 4 545 6 7 8 9 550 1 2 3 4 545 6	OVERALL RATING - SPEED LIMIT SIGN - STRIPING - HAZARD MARKER - AERIAL SIGNAL - WARNING DEVICE - CLEARANCE SIGN - BARRIERS & GATES - LEGIBILLTY - VISIBILITY - NAVIG. LIGHTS - OVERALL RATING - OVERALL STR. RATING - OVERALL	INSPECTION DATA	LOUISIANA DEPARTMENT OF HIGHWAYS RECORD LAYOUT SH
621 	0 2 3 4 5 6 7 8	DATE ATEST	REPAIRS	555 6 7 8 9 560	DATE OF INSPECTION RECOMMENDED DATE OF NEXT INSPECTION	INSPECTION DATES	SHEET STRUCTURES
636 	9	TYPE TYPE TYPE EXTRA SPACE TOTAL REPAIRS	**	565 6 7 8 9 570 1 2 3	MATERIAL STRUC. CONDITION DECK GEOMETRY UNDERCLEARANCES SAFE LOAD CAPACITY WATERWAY ADEQ. APPRO. RDWY. ALIGN. YEAR NEEDED	GUARD- APPRAISAL	Page 5 of 6



APPENDIX D

MASTER STRUCTURE FILE CODES	Page D-1
SPECIAL CODING INSTRUCTIONS FOR	
SUPPLEMENTAL FIELD DATA	D-28
STRUCTURE INVENTORY AND APPRAISAL SHEET	D-29
SPECIFIC DATA TO BE PROVIDED BY SECTIONS	D-33

MASTER STRUCTURE FILE CODES

IDENTIFICATION

RECALL NUMBER - Columns 1-6

A unique 6 digit number for each structure.

CONTROL NUMBER - Columns 7-9

Code the control number, assigned by Project Control, of the section of road being coded. Prefix the code with zeros to complete the field.

SECTION NUMBER - Columns 10-11

Code the section number, assigned by Project Control, of the control being coded. Prefix with zeros to complete the field.

LOG MILE - Columns 12-15

The log mile location is the distance from the beginning of the control section to the structure being coded. Record this distance in these columns prefixing enough zeros to form a 4-digit code.

BRIDGE I.D. - Column 16

Code one of the following numbers in this field:

Right Main Roadway 1

Left Main Roadway 2

Right Frontage Road 3

Left Frontage Road

When on a two-lane highway, the number should be "1". When traveling under an underpass the number should also be "1" unless it only involves the left roadway of a divided highway in which case the number should be "2".

FLAGS

STRUCTURE COUNT - Column 17

Code (*) if the structure is to be counted with this control section.

BRIDGES FOR DEFENSE - Column 18

Code (*) if bridge for defense.

MAJOR BRIDGES - Column 19

Code (*) if designated major.

UNDER 20 FEET - Column 20

Code (*) if bridge is not 20 feet long.

BRIDGES FOR DEFENSE

SECTION NUMBER - Columns 21-23

As required by "Bridges for Defense".

BRIDGE LETTER - Columns 24-27

As required by "Bridges for Defense".

SECTION MILE POST - Columns 28-31

As required by "Bridges for Defense".

SECTION LENGTH - Columns 32-34

As required by "Bridges for Defense".

LOCATION

STATE ROUTE NUMBER - Columns 35-42

Code the interstate, U.S., state, or other highway route number.

FEDERAL ROUTE NUMBER - Columns 43-45

Code the federal route number.

DISTRICT - Columns 46-47

Code the number of the "Highway Construction and Maintenance District" in which the structure is located.

PARISH - Columns 48-49

Code the number assigned to the parish in which the structure is located.

CITY

STATE CODE NO. - Columns 50-51

When structures are within incorporated places or within delimited unincorporated areas it will be necessary to code the number assigned to that place.

NATIONAL GEOGRAPHIC CODE NO. - Columns 52-55

As coded by 1970 U.S. Census Geographic coding scheme.

PLACE CLASS - Column 56

- Code 1 Rural areas.
 - 2 In incorporated places under 2500 population.
 - 3 In incorporated places between 2500 4999 population.
 - 4 In incroporated places between 5000 9999 population.
 - 5 In incorporated places between 10,000 24,999 population.
 - 6 In incorporated places between 25,000 49,999 population.
 - 7 In incorporated places between 50,000 99,999 population.
 - 8 In incorporated places 100,000 population and over.
 - 9 In approved urban unincorporated areas adjacent to places of 5000 or more population.
 - 0 In other delimited urban unincorporated places.

STATE - Column 57

- Code 1 Interstate (Fed. aid interstate).
 - 2 Primary (designated by Legislature as State primary).
 - 3 Secondary (designated by Legislature as State secondary).
 - 4 Farm-To-Market (designated by Legislature as State farm-to-market).
 - 7 Local (all public roads, rural and urban, that are not part of the State maintained system).

FEDERAL - Column 58

- Code I Interstate (Fed. aid interstate).
 - P Primary (Fed. aid primary).
 - S Secondary (Fed. aid secondary).

If not on any federal aid system, leave blank.

U.S. NUMBERED - Column 59

Code a U if the structure is on a road which is part of the US Numbered System of Highways. If not, leave columns blank.

MAINT. BY - Column 60

- 1 State funded and maintained
- 2 Partially State funded and State maintained.
- 3 Not State funded and State maintained.
- 4 Funded and maintained by other agency.

TOLL - FREE - Column 61

If there is a toll for crossing this structure, code a "1" in this column. If not leave blank.

SHARED COST - Column 62

Code an (*) if the operation and/or maintenance costs are to be shared by LDH and some other agency.

LATITUDE - Columns 63-67

Enter latitude in degrees, minutes, and tenths of minutes.

LONGITUDE - Columns 68-73

Enter longitude in degrees, minutes, and tenths of minutes.

TRAFFIC

CURRENT ADT - Columns 74-77

Code to nearest 10 vehicles.

NUMBER OF TRAFFIC LANES - Column 78

Code actual number of traffic lanes.

NUMBER OF SAFETY LANES - Column 79

Code actual number of safety lanes.

NUMBER OF LANES CROSSED - Columns 80-81

Code actual number of traffic lanes of the roadway being intersected.

DESCRIPTION

DIVIDED-TWIN - Column 82

If opposing traffic on the structure is physically separated by means of barrier curb, bridge superstructure, raised median, etc., place "D" in this column. For parallel structures (each carrying traffic in opposite directions) place "R" (Right) for the structure in the direction of inventory and "L" (Left) for the structure in the opposite direction of inventory. If none of the above situations exist, leave this column blank.

TYPE CODE - Column 83-84

As given in Control Section Manual.

PHYSICAL VULNERABILITY - Column 85

Timber trestle Code - 1

Concrete girder Code - 2

Steel girder Code - 3

Cantilever and truss Code - 4

Suspension	Code -	5
Reinforced concrete - massive arch	Code -	6
Dam bridge	Code -	7
Box culverts	Code -	8
Tunnels	Code -	9
No structure	Code -	0

MATERIAL

SUPERSTRUCTURE - Column 86

Code the material or combination of materials in the superstructure including everything above the caps or piers except the floor.

MATERIAL - CODES FOR SUBSTRUCTURE-SUPERSTRUCTURE

1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	_
0	_
	3 4 5 6 7 8

PIERS - Column 87

Same codes as superstructure.

ABUTMENTS - Column 88

Same codes as superstructure.

PILES - Column 89

Same codes as superstructure.

FOUNDATION - Column 90

Same codes as superstructure.

FLOOR - Column 91

Code the material or combination of material in the floor.

MATERIAL	CODE
Untreated Timber	1
Untreated Timber - Steel Traffic Plates	2
Treated Timber	3
Treated Timber - Steel Traffic Plates	4
Steel Grill	5
Corrugated Steel - Asphalt	6
Concrete Reinforced	7

RIDING SURFACE - Column 92

- 1 Soil, Dirt, etc.
- 2 Gravel, Shell, etc.
- 3 Bituminous Low type
- 4 Bituminous High type
- 5 Bituminous Concrete
- 6 Light weight concrete
- 7 Portland cement concrete
- 0 Same as floor of structure

SURFACE THICKNESS - Column 93-94

Code to nearest half inch.

DRAW SPAN

Type - Column 95

Indicate the type of draw span using the following codes:

- Code 1 Single leaf bascule
 - 2 Double leaf bascule
 - 3 Vertical lift
 - 4 Rotary (Swing)
 - 5 Pontoon (Swing)
 - 6 I-Beam (Lift out)

- 7 Boat (On ferries only)
- 8 Barge (On ferries only)
- 9 High level fixed crossing

Operation - Column 96

Code the type of operation of draw span using the following codes:

- Code 1 Hand operated
 - 2 Power operated
 - 3 Free floating (Ferries)
 - 4 Cable drawn (Ferries)

PROTECTION - Column 97

Indicate the protection at the structure or crossing using the following codes:

- Code 1 Signs only
 - 2 Bells only
 - 3 Wigwag with lights
 - 4 Wigwag with lights and bells
 - 5 Flashing lights only
 - 6 Flashing lights and bells
 - 7 Chain or cable
 - 8 Gates or barriers
 - 9 Watchman only
 - X No protection, where protection is needed

AVERAGE MONTHLY OPENINGS (MOVABLE) - Columns 98-101

Average monthly openings from data of previous year.

SECTION - Column 102

Code "1" for structures on the main roadway and "4" for frontage road structures.

TOTAL LENGTH - Columns 103-108

Code actual linear feet with leading zeros.

MAX. SPAN LENGTH - Columns 109-112

Code length in actual linear feet of the longest span.

NUMBER OF SPANS - Columns 113-116

Code actual number of spans in the structure.

FIRST EXTRA

Description of main span when different from approaches.

Section - Column 117

Code "2" when main span is different from approaches.

Structure Code - Columns 118-119

Code type of main span.

No. of Spans - Columns 120-122

Code the number of main spans.

Max. Span Length - Columns 123-125 (P)

Code the length in feet of the longest main span. (Packed)

SECOND THRU NINTH EXTRA - Columns 126-197

Description of approach spans when different from main span. Same configuration as first extra. Code same as first extra except section should be coded "3".

CAPACITY DATA

DESIGN LOAD - Columns 198-199

Code actual tons with leading zeros.

OPERATING RATING - Columns 200-202

Record for the critical vehicle the operating rating as explained in Section 4.1 of the AASHO Manual for Maintenance Inspection of Bridges, 1970. A three-digit code should be used. The first digit will show the type of loading.

H truck

6 3-3 trailer

2 HS truck

- 7 Railroad loading
- 3 Alternate Interstate loading 8 Pedestrian or special loading
- 4 3-Axle truck (type 3) 9 Gross load only given
- 3-S semi-trailer 5

The second and third digits will give the gross loading in tons, except pedestrian and railroad loading. For railroad loading only, the second and third digits will give Cooper Class or equivalent load. Code pedestrian loading as: "800". Example:

3-S semi-trailer, 72000 pounds code 536 INVENTORY RATING - Columns 203-205

Record for the critical vehicle the inventory rating as explained in Section 4.1 of the AASHO Manual for Maintenance Inspection of Bridges, 1970. A three-digit code should be The first digit will show the type of loading:

1 H truck 6 3-3 trailer

2 HS truck

- 7 Railroad loading
- 3 Alternate Interstate loading 8 Pedestrian or special loading
- 4 3-axle truck (type 3) 9 Gross load only given
- 3-S semi-trailer

The second and third digits will give the gross loading in tons, except pedestrian and railroad loading. For railroad loading

only, the second and third digits will give Cooper Class or equivalent load. Code pedestrian loading as "800".

Example:

3-S semi-trailer, 72000 pounds code 536

POSTED LOAD LIMIT - Columns 206-207

Code posted load in tons.

POSTED SPEED LIMIT - Columns 208-209

Code posted speed in MPH.

DESIGN ADT - Columns 210-212

Code to nearest 100 vehicles with leading zeros.

CLEARANCES

STRUCTURE FLARED - Column 213

If the horizontal clearance is not consistent, code "1" in this column. Otherwise, leave blank.

ROADWAY

Horizontal

Minimum Roadway

Single Structure or Right - Column 214-216

Code to nearest tenth of a foot for minimum curb to curb or shoulder to shoulder.

Left - Columns217-219

Code to nearest tenth of a foot for minimum curb to curb or shoulder to shoulder.

Railing to Railing

Single Structure or Right - Columns 220-222

Code to nearest tenth of a foot.

<u>Left - Column 223-225</u>

Code to nearest tenth of a foot.

RAILINGS - TYPE - Column 226

Use following codes:

- 1 Parapet
- 2 Barrier
- 3 Brush

RAILINGS - MATERIAL - Columns 227-228

Use following codes:

- 1 Aluminum
- 2 Aluminum and concrete
- 3 Concrete
- 4 Concrete and steel
- 5 Steel

SIDEWALKS

NUMBER - Column 229

Code actual number of sidewalks on structure.

WIDTH - Column 230-231

Code width to nearest tenth of a foot. If there are two sidewalks with two different widths, code the wider of the two.

SIDE - Column 232

Code "R" or "L" if a sidewalk is on the right or left of the structure. If on both sides, code "B".

MAXIMUM STRUCTURE WIDTH - Columns 233-236

Code to nearest tenth of a foot.

MAXIMUM OH WIDTH AT MAX. VERTICAL - Columns 237-239

Code to nearest tenth of a foot.

TOTAL SHOULDER WIDTH (UNDERPASS) - Columns 240-242

Code to nearest foot.

MEDIAN TYPE - Column 243

Use the following codes:

- 1 Curb
- 2 Wall
- 3 Guardrail
- 4 Fence
- 5 Bridge superstructure
- 6 Open (Twin structures)
- 7 Couplet
- 8 Painted median
- 9 Painted stripe
- 0 No Median

MEDIAN WIDTH - Columns 244-245

Code to nearest foot. If median exceeds 99 feet, code "99".

VERTICAL

MINIMUM AT CENTERLINE - Columns 246-249

Code feet in first two columns and inches in last two columns with leading zeros for each.

MINIMUM AT RIGHT CURB - Columns 250-253

Code same as for centerline.

MINIMUM AT LEFT CURB - Columns 254-257

Code same as for centerline.

MINIMUM WITH ROADWAY - Columns 258-261

Code same as for centerline.

WATERWAY (UNDER STRUCTURE)

VERTICAL - Columns 262-265

Code same as for centerline of main roadway.

HORIZONTAL (RIGHT) - Columns 266-268

Code to nearest foot.

HORIZONTAL (LEFT) - Columns 269-271

Code to nearest foot.

MINIMUM CHANNEL - Columns 272-274

Code to nearest foot.

MINIMUM PIER TO PIER - Columns 275-277

Code to nearest foot.

REFERENCE ELEVATION - Columns 278-280

Code to nearest foot.

MINIMUM VERTICAL FROM REFERENCE ELEVATION - Column 281-284

Code to nearest foot.

CROSSING DATA

FACILITY TYPE CODE - Column 285

- B For bridge
- C For overhead pipeline or conveyor
- E For elevated roadway
- F For ferry
- I For interchange
- 0 For overpass highway or railroad
- R Overhead sign
- S For subway
- T For tunnel
- U For underpass highway or railroad
- W Pedestrian overpass

KIND OF CROSSING - Columns 286-287

Use two digit code as follows:

CODE	FIRST DIGIT ON STRUCTURE	SECOND DIGIT UNDER STRUCTURE
1	Highway	Highway
2	Railroad	Railroad
3	Pedestrian	Pedestrian
4	Highway - RR	Highway - RR
5	2nd level - interchange	Waterway
6	3rd level - interchange	Highway - Waterway
7	4th level - interchange	RR - Waterway
8	Building or Plaza	Highway - RR - Waterway
9	Other (see remarks)	Other

FUNCTION CODE - Columns 288-289

As required by "Damage Assessment".

RAILROAD CODE - Columns 290-291

If a railroad is either overpassed or underpassed, enter code for the name of railroad as shown in the Road Inventory Manual of the Traffic and Planning Section.

FEATURE CROSSED - Columns 292-308

Identifying names (streams, roads, railroads, etc.) and descriptive remarks.

RESERVED SPACE - Columns 309-316

Leave these columns blank.

BYPASS DETOUR LENGTH - Columns 317-318

If it is possible to bypass the structure at the site, code "BP".

Otherwise, code to the nearest mile the travel distance required to bypass the structure.

GEOMETRICS

APPROACH ROADWAY WIDTH - Columns 319-321

Code to the nearest foot.

ALIGNMENT

CURVE OR TANGENT - Column 322

- 1 Curve
- 2 Tangent

RADIUS IF CURVED - Columns 323-326

Code radius to nearest tenth of foot with leading zeros.

SKEW ANGLE - Columns 327-328

Code to nearest degree with leading zeros.

HYDRAULIC DATA

HIGH WATER MARK - FROM REF. ELEV. - Columns 329-332

Code to nearest tenth of foot.

WATERWAY CLASS - Column 333-334

Code to be determined.

NORMAL STREAM VELOCITY - Columns 335-336

Code to nearest Ft. per second.

STREAM BED MATERIAL - Columns 337-338

Codes to be determined.

RELIEF STRUCTURE - Columns 339-340

If this structure is one of several in a given flood plain required to handle the design flood, give the number of such structures. Code the number as a 2 digit number.

HYDRO. SURVEY MICRO. INDEX - Columns 341-344

Code to be determined.

DATE OF LAST HYDRO. SURVEY - Columns 345-348

Code month, and last two digits of year as MMYY with leading zeros as required.

RATING OF LAST HYDRO. SURVEY - Columns 349-350

Code to be determined.

OPENING - Columns 351-356

Actual area in square feet bounded by bottom of structure, banks of feature crossed, and bottom of feature crossed.

AREA - Columns 357-360

Area drained in square miles.

MATERIAL QUANTITIES

CONCRETE - Columns 361-364

Code to nearest cubic yard with leading zeros.

DEFORMED STEEL - Columns 365-369

Code to nearest ton with leading zeros.

STRUCTURAL STEEL - Columns 370-374

Code to nearest ton with leading zeros.

ENCROACHMENTS - Column 375-384

Code the number of utilities attached to the structure as follows:

TYPE UTILITY	COLUMN
Power	375
Communication	376
Petroleum Products	377
Water	378
Sewer	379

Code the number of utilities crossing the R/W near the structure as follows:

TYPE UTILITY	COLUMN
Power	380
Communication	381

Petroleum	Products	382
Water		383
Sewer		384

PLANS DATA

PROJECT NUMBER CONSTRUCTED UNDER - Columns 385-393

Code 7 digit project numbers as XXX-XX-XX (prefixing each section with leading zeros where necessary and including dashes). Code older project numbers in free format beginning in first column.

TYPE PLANS AVAILABLE - Columns 394-395

- 1 Design Plans
- 2 Right of Way
- 3 Construction
- 4 As Built
- 5 Ozlid
- 6 Blue Print
- 7 Shop Drawing
- 8 Tracing
- 9 Standard Plan
- 10 Cross Section
- 11 Drainage
- 12 Aerial Photographs
- 13 Subgrade Soil Survey
- 14 Hydrographic Survey

AS BUILT? - Column 396

- 1 Plans are as built.
- 2 Plans are not as built.

WHERE FILED - Columns 397-398

Code to be determined.

STRUCTURE COST - Columns 403-411

Code total cost in dollars with leading zeros.

STRESS ANALYSIS

DATA AVAILABLE - Column 412

1 - Yes

2 - No

WHERE FILED - Columns 413-414

Code to be determined.

DATE STRUCTURE COMPLETED - Columns 415-418

Code month and last 2 digits of year.

DATE OF MAJOR RECONSTRUCTION - Columns 419-422

Code month and last 2 digits of year.

DATE OF DATA INVENTORY - Columns 423-428

Code month, day, and last 2 digits of year as MMDDYY showing leading zeros for each as required.

MAINTENANCE INSPECTION DATA

Enter codes as prescribed by <u>Manual for Maintenance Inspection of Bridges - 1970</u> prepared and published by AASHO. Enter a code 0-9 in each column from 429 through 524 and in column 525 for overall structure rating.

SUPERSTRUCTURE - Columns 429-450

MOVABLE SPANS - Columns 451-457

DECK - Columns 458-469

SUBSTRUCTURE - Columns 470-490

APPROACHES - Columns 491-501

WATERWAY - Columns 502-512

TRAFFIC SERVICES - Columns 513-523

TOTAL RATING - Column 524

OVERALL STRUCTURAL RATING - Column 525

RESERVED SPACE - Columns 526-556

Leave these columns blank. This space is reserved for future inspection data.

DATE INSPECTED - Columns 557-560

Code 2 digit month and last 2 digits of year.

RECOMMENDED DATE NEXT INSPECTION - Columns 561-564

Code same as above.

GUARDRAIL TYPE - Columns 565-566

Code to be determined.

GUARDRAIL MATERIAL - Column 567

Code to be determined.

APPRAISAL - Columns 568-573

STRUCTURE CONDITION - Column 568

Describe major structural deficiencies, giving rating of critical item(s).

DECK GEOMETRY - Column 569

Describe adequacy of roadway width, clearances above deck, etc.

UNDERCLEARANCES - Column 570

Vertical and Horizontal under clearance from thru roadway to superstructure and substructure units, respectively.

SAFE LOAD CAPACITY - Column 571

Describe deficiencies, determine safe load capacity and adequacy.

WATERWAY ADEQUACY - Column 572

Describe waterway inadequacies, i.e., scour, erosion, slope protection, capacity, etc.

APPROACH ROADWAY ALIGNMENT - Column 573

Identify inadequate approach alignment conditions.

The following codes will be used to describe major deficiencies.

RATING	EXPLANATION
9	Conditions superior to present desirable criteria.
8	Conditions equal to present desirable criteria.
7	Condition better than present minimum criteria.
6	Condition equal to present minimum criteria.
5	Condition somewhat better than minimum adequacy to
	tolerate being left in place as is.
4	Condition meeting tolerable limits to be left in
	place as is.
3	Basically intolerable condition requiring high
	priority of repair.
2	Basically intolerable condition requiring high
	priority in replacement.
1	Immediate repair necessary to put back in service.
0	Immediate replacement necessary to put back in service.

PROPOSED IMPROVEMENTS

YEAR NEEDED - Columns 574-575

Code the last two digits of the year of the proposed improvements.

TYPE SERVICE - Column 576-577

See Kind of Crossing - Columns 286-287.

TYPE WORK - Column 578-580

Codes to be determined.

LENGTH OF IMPROVEMENT - Columns 581-585

Code the length (in feet) of the proposed improvement.

PROPOSED DESIGN LOAD - Column 586-587

Code the design load in tons with leading zeros.

PROPOSED ROADWAY WIDTH - Columns 588-590

Code to nearest foot.

PROPOSED NUMBER OF LANES - Columns 591-592

Code the number of lanes of the proposed improvement.

PROPOSED A.D.T. - Columns 593-595

Code the A.D.T. which controls now design.

YEAR OF A.D.T. - Column 596-597

Code last two digits of the year of the A.D.T. estimate.

YEAR OF ADJACENT IMPRO. - Columns 598-599

Code last two digits of the year in which improvements to the roadway approaches to the bridge will take place.

TYPE ADJ. IMPROVEMENT - Column 600

Use following codes:

- 0 Not applicable
- 1 Resurface
- 2 Reconstruct
- 3 Widening
- 4 Shoulder improvements
- 5 Other (explain in remarks)

COST OF PROPOSED IMPRO. - Columns 601-604

Code the estimated cost to the nearest hundred dollars of the proposed improvement.

REPLACEMENT PRIORITY - Columns 605-610

Code the most critical structure as "001", the least as "999" by district in columns 605-607 and by state in columns 608-610.

REPA IRS

LAST FIVE REPAIRS - Columns 611-635

COLUMNS 611-614

Code month and year of latest repair.

COLUMN 615

Code type of latest repair.

COLUMNS 616-619

Code month and year of 2nd latest repair.

COLUMN 620

Code type for 2nd latest repair.

COLUMNS 621-624

Code month and year of 3rd latest repair.

COLUMN 625

Code type for 3rd latest repair.

COLUMNS 626-629

Code month and year of 4th latest repair.

COLUMN 630

Code type for 4th latest repair.

COLUMNS 631-634

Code month and year of 5th latest repair.

COLUMN 635

Code for 5th latest repair.

Repair Codes are as follows:

Erosion or Scour	A
Fender System	В
Piling	C
Piers	D
Caps	E
Stringers or Girders	F
Decks	G
Resurfacing	H
Handrail	1
Bearings Areas	J
Expansions	K
Approaches	L
Abutments	M
Settlements	N
Steel Truss - Major Members	0
Steel Truss - Secondary Members	P
Steel Truss - Overhead Members	Q
Mechanical	R
Electrical	s
Greasing & Servicing	T
Painting	U

EXTRA SPACE - Column 636

NUMBER OF REPAIRS - Columns 637-638

Code total number of repairs to structure since construction.

PAINT REQUIREMENTS

PROJECT NUMBER FOR PAINT JOB - Columns 639-647

Code 7 digit Project No. as XXX-XX-XX (prefixing each section with leading zeros where necessary and including dashes). Code older project numbers in free format beginning in first column of field.

PAINT SYSTEM - Columns 648-649

Enter code for system used.

DATE PAINT JOB COMPLETED - Columns 650-653

Code 2 digit month and last 2 digits of year.

PAINTED BY - Columns 654-668

Code name of contractor or organization.

CLEANING METHOD - Column 669

- Code 1 Hand tool cleaning
 - 2 Power tool cleaning
 - 3 Commercial blast cleaning
 - 4 Near white blast cleaning
 - 5 White metal blast cleaning

QUANTITY OF PAINT REQUIRED - Columns 670-676

Code in gallons with leading zeros.

COLOR - Columns 677-678

Color codes to be determined.

NUMBER OF COATS - Column 679

Code actual number of coats.

COST OF PAINT JOB - Columns 680-685

Code to nearest dollar with leading zeros.

STRUCTURE NUMBER - Columns 686-695

The number that is painted on the structure (same as col. 7-16 in most cases).

EXTRA SPACE - Column 696

CONTRACT OR DISTRICT - Column 697

"C" if built under contract.

"D" if built by district.

Blank if unknown.

EXTRA SPACE - Column 698

ENVIRONMENTAL CONDITIONS - Columns 699-700

Use the following codes to describe the normal environment to which the structure is subjected.

- 1 Corrosive chemical atmosphere
- 2 Salt water
- 3 Acid water from plant
- 4 High humidity
- 5 Electrical plant (Galvanic corrosion)
- 6 Cathodic protection
- 7 Large flood plain
- 8 Swift current tidal current
- 9 Vermin
- 10 Freezing (salt action)
- 11 Collision and overloads (industrial & commercial hauling)
- 12 Dense traffic
- 13 Pedestrian
- 14 Strong winds (hurricanes)

FUNCTIONAL CLASSIFICATION - Columns 701-702

Use the functional classification code for the section as determined and assigned for the Functional Classification Study. It is suggested that the 1990 classification code be used. The codes given below are for that year.

Population	5-10	10-25	25-50	50+		
	11	21	31	41	Interstate	01
	12	22	32	42	Other Freeway &	
					Expressway	
	13	23	33	43	Other Principal	02
					Arterial	
	14	24	34	44	Minor Arterial	03
	15	25	35	45	Collector	-
	~		-	-	Major	04
	~		-	-	Minor	05

DISTRICT MT. BY - Columns 703-704

Code the DISTRICT THAT ACTUALLY maintains the structure.

REMARKS - Columns 705-716

Code anything necessary to aid in describing the structure.

SPECIAL CODING INSTRUCTIONS FOR SUPPLEMENTAL FIELD DATA

RECALL NUMBER - Column 1-6, Line 1, 2, 3

Code the recall number of the structure being coded taken from the Control Section manual - Volume II.

If a new structure is encountered in the field that is not in the manual, add 2 to the recall number of the previous structure and code the new number in this space.

If it is found that a structure in the manual does not actually exist, omit that recall number. Do not use that number for another structure.

POSTED SPEED LIMIT - Columns 27-28, Line 1

Code the speed limit posted on the structure. If no speed limit is posted, code the speed limit of the road on which the structure is located.

MEDIAN WIDTH - Columns 56-58, Line 1

The first digit of this field will be used to designate the type of median as explained in the coding manual. The last two digits will be used to code the width to the nearest foot.

REFERENCE ELEVATION - Columns 24-26, Line 2 This field will not be coded.

VERT. CLEARANCE FROM REF. ELEV. - Column 27-30, Line 2

This field will be used to indicate the vertical clearance between low steel and water when at normal level.

HIGHWATER MARK FROM REF. ELEV. - Column 60-63, Line 2

Code the vertical clearance between low steel and high water.

STRUCTURE INVENTORY AND APPRAISAL SHEET

HOW OBTAINED	ITEM NO.	ITEM NAME	MASTER FILE LOCATION
+	1	State (Programmed)	Known
4	2	District	46-47
+	3	Parish	48-49
+ TP	4	City (Programmed)	52-55
+	5	Route	35-42
+ MI, PC	6	Feature Crossed	292-308
+	7	Facility Carried	285
+ PC	8	Structure Number	7-16
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	9	Location (Narrative) (Not required)	toda may typic mine artis
+	10	Control Section	7-11
+	11	Milepost	12-15
+	12	DOD Section Number	21-23
+	13	DOD Bridge Letter	24-27
+	14	DOD Milepost	28-31
+	15	DOD Section Length	32-34
+	16	Latitude	63-67
+	17	Longitude	68-73
+	18	Physical Vulnerability	85
MT	19	Bypass Detour Length	317-318
TP	20	Toll (Very few in state)	61
+	21	Custodian	60
÷	22	Owner	60
A-4 707 GB; 459	23	Federal-Aid Project number (not required)	Not in file
+	24	Federal System (programmed)	58 & 56

HOW OBTAINED	ITEM NO.	ITEM NAME	MASTER FILE LOCATION
+	25	Administrative Jurisdictions	60
ТР	26	Functional Class	701-702
+	27	Year Built	417-418
MT	28	Lanes on/under Structure	78-79 + 80-81
TP	29	ADT	74-77
TP	30	Year of ADT (not required)	427-428
+	31	Design Load	198-199
MT	32	Approach Roadway Width	319-321
MT	33	Median	243
MT	34	Skew	327-328
MT	35	Structure Flared	213
	36	pas and any pair also also also has now have been fine fine	
	37		-
BD	38	Navigation Control	333-334
MT	39	Navigation Vertical Clearance	281-284
MT	40	Navigation Horizontal	272-274
	41		
PROG.	42	Type Service	286-287
+	43	Type Main Span	83-84
+	44	Type Approach Span	127-128
+	45	Number of Main Spans	120-122
+	46	Number of Approach Spans	129-131
~~~	47		1980 Title Clay clay case and and rese
+	48	Length of Maximum Spans	109-112
+	49	Structure Length	103-108
MT	50	Sidewalk Width/Side	230-232
MT	51	Bridge Width, Curb/Curb	214-216
MT	52	Bridge Width, Out/Out D-30	217-219 233-236

HOW OBTAINED	ITEM NO.	ITEM NAME	MASTER FILE LOCATION
+ MT	5 <b>3</b>	Minimum Vertical Clearance	258-261
MT	54	Minimum Vertical Underclearance	262-265
MT	55	Minimum Lateral Under Right	266-268
МТ	56	Minimum Lateral Under Left	269-271
MT	57	Wearing Surface	92
MI	58	Condition - Deck	469
MI	59	- Superstructure	450
MI	60	- Substructure	490
MI	61	- Channel	497
MI	62	- Culverts	497
MT	63	Estimated Remaining Life	574-575
BD	64	Operating Rating	200-202
MT	65	Approach Roadway Alignment	322
BD	66	Inventory Rating	203-205
MI	67	Appraisal - Structural Condition	568
MT	68	- Deck Geometry	9
MT	69	- Underclearances	70
MT	70	- Safe Load Capacity	71
MT	71	- Waterway Adequacy	72
MT	72	- Approach Roadway Alignment	73
MT	73	Proposed Improvements - Year Needed	<b>574-7</b> 5
MT	74	- Type of Service	576-77
MT	75	- Type of Work	578-80
MT	76	- Length	581-85
MT	77	- Proposed Design Load	586-87

HOW OBTAIN	ITEM NO.	ITEM NAMI	<u>E</u>		MASTER FILI LOCATION
MT	78	Proposed	Improvements	- Proposed Width	588-90
MT	79			- Proposed No. Lanes	591-92
MT	80			- Design ADT	593-95
MT	81			- Year of ADT Est.	596-97
MT	82			- Year of Adj. Imp.	598-99
MT	83			- Type Adjacent Imp	. 600
MT	84			- Cost	601-604
+	Presently	in file			30
MT	Coded by Ma	aintenance	on Form MT-1		35
MI	Coded by Ma	aintenance	on Form 3097		6
BD	Coded by B	ridge Desig	gn on Form BD	-1	3
PC	Coded by P	roject Cont	trol on Form	PC-1	0
TP	Coded by T	raffic & Pl	anning		4
	Not Require	ed			6
					84

## BRIDGE DESIGN

MASTER RECORD COL. #	FIELD NAME	LENGTH	S, I, & A ITEM NO.
19	Major Bridge Flag	1	
200-202	Operating Rating	3	64
203-205	Inventory Rating	3	66
210-212	Design ADT	3	
333-334	Waterway Class	2	38
335-336	Normal Stream Velocity	2	
337-338	Stream Bed Material	2	
339-340	Relief Structure	2	
341-344	Hydro Survey Micro Index	4	
345-348	Date Last Survey	4	
349-350	Rating	2	
351-356	Drainage Opening	6	
357-360	Area Drained	4	
	Quantities (New only)		
361-364	Concrete	4	
365-369	Deformed Steel	5	
370-374	Structural Steel	5	
412	Stress Analysis Data	1	
413-414	Where Filed	1	

## PROJECT CONTROL

MASTER RECORD COL. #	FIELD NAME	LENGTH	S, I, & A ITEM NO.
16	Bridge ID (1, 2, 3, 4)	1	8
62	Shared Cost	1	
292-308	Feature Crossed	17	6
385-393	State Project Number	9	
394-395	Type Plans	2	
403-411	Cost of Structure	9	
		,	
611-615	Latest Repair	5	
616-620	2nd Latest Repair	5	
621-625	3rd Latest Repair	5	
626-630	4th Latest Repair	5	
631-635	5th Latest Repair	5	
697	Contract - District	1	

## PROJECT CONTROL

MASTER RECORD COL. #	FIELD NAME	LENGTH	S, I, & A ITEM NO.
396	As Built	1	
397-398	Where Filed	2	
419-422	Date of Major Reconstruction	4	
637-638	Total Repairs	2	
639-647	Paint Proj. No.	9	
648-649	System	2	
650-653	Date Camp	4	
654-668	Ву	15	
669	Cleaning Method	1	
670-676	Quantity	7	
677-678	Coļor	2	
679	No. of Coats	1	
680-685	Cost	6	

#### MA INTENANCE

MASTER RECORD COL. #	FIELD NAME	LENGTH	S, I, & A ITEM NO.
565-66	Guardrail Type	2	
567	Guardrail Material	1	
20	Under 20' Flag	1	
697-700	Environmental Conditions	2	
703-716	Remarks	14	

## TRAFFIC & PLANNING

MASTER RECORD COL. #	FIELD NAME (UPDATE PROGRAM)	LENGTH	S, I, & A ITEM NO.
74-77	ADT	4	29
423-428	Date of Inventory (ADT)	6	30
61	Toll	1	20
52-55	City (Programmed)	4	4
701-702	Functional Class	2	26

## SUPPLEMENTAL FIELD DATA

MASTER RECORD	FIELD NAME	LENGTH	S, I, & A ITEM NO.
1-6	Recall Number	6	
78	Number of Traffic Lanes	1	28
79	Number of Safety Lanes	1	28
80-81	Number of Lanes Crossed	2	28
86	Material - Substructure	1 .	59
87	- Piers	1	
88	- Abutment	1	
89	- Piles	1	
90	- Foundation	1	
91	- Floor	1	
92	- Riding Surface	1	
93-94	Surface Thickness	2	
98-101	Average Monthly Openings	4	
206-207	Posted Load Limit	2	
208-209	Posted Speed Limit	2	
213	Structure Flared	1	
	HORIZONTAL CLEARANCE		
214-216	Right Curb/Curb	3	51
217-218	Left Curb/Curb	3	51
220-222	Right Rail/Rail	3	52
223-225	Left Rail/Rail	3	52
233-236	Out to Out Width	4	52

## SUPPLEMENTAL FIELD DATA (Continued)

MASTER RECORD COLUMN NO.	FIELD NAME	LENGTH	S, I, & A ITEM NO.
226	Railing Type	1	
227-228	Material	2	
229	Sidewalks Number	1	
230-231	- Width	2	50
232	- Side	1	50
240-242	Total Shoulder Width	3	
243	Median Type	1	53
244-245	Median Width	2	33
	VERTICAL CLEARANCE		
254-257	Left Curb	4	53
246-249	Centerline	4	53
250-253	Right Curb	4	53
	CLEARANCES UNDER STRCUTURE		
262-265	Vertical	4	54
269-271	Horizontal Left	3	56
266-268	Horizontal Right	3	55
272-274	Channel Width	3	40
<b>275–2</b> 77	Pier to Pier	3	
281-284	Vertical Clearance from Reference Elevation	4	39
292-308	Feature Crossed	17	6
317-318	Bypass Detour	2	19
319-321	Approach Roadway Width	3	32

## SUPPLEMENTAL FIELD DATA (Continued)

MASTER RECORD	FIELD NAME	LENGTH	S, I, & A ITEM NO.
322	Alignment	1	65
323-326	Radius of Curve	4	
327-328	Skew Angle	2	34
329-332	High Water Mark from Refe Elevation	erence	
	ENCROACHMENTS		
<b>3</b> 75	Attached to Bridge - 1st	1	
376	- 2nd	1	
377	- 3rd	1	
378	- 4th	1	
379	- 5th	1	
380	Crossing R/W - 1st	1	
381	- 2nd	1	
382	- 3rd	1	
383	- 4th	1	
384	~ 5th	1	
	APPRAISAL		
569	Deck Geometry	1	<b>6</b> 8
570	Underclearances	1	69
571	Safe Load Capacity	1	70
572	Waterway Adequacy	1	71
573	Approach Roadway Alignmen	t 1	72

## SUPPLEMENTAL FIELD DATA (Continuted)

MASTER RECORD	FIELD NAME	LENGTH	S, I, & A ITEM NO.									
PROPOSED IMPROVEMENTS												
574-575	Year Needed	2	73									
576-577	Type Service	. 1	74									
578-580	Type of Work	3	75									
581-585	Length of Improvement	6	76									
586-587	Proper Design Load	1	77									
588-590	Proper Roadway Width	4	78									
591-592	Number of Lanes	2	79									
593-595	Design ADT	3	80									
596-597	Year of Estimate	2	81									
598-599	Year of Adjacent Improvements	2	82									
600	Type of Adjacent Improvements	1	83									
601-604	Cost	4	84									
605-607	District Priority	3										
608-610	State Priority	3										
	LOCATION											
547-551	Central Section	5	8									
552-555	Log Mile	4	8									
556	Bridge I.D.	· 1	8									
	District	2										
	Parish	2										

# APPENDIX E COMPUTER PRINTOUT FORM

LA. DEPT. OF HIGHWAYS MASTER STRUCTURE FILE PARISH

DISTRICT

RECALL NUMBER

STRUCTURE NUMBER

TRAFFIC	A D.T. Mediest 10 Veh. 10 Veh. 1164. Lanes			Spans A May of I I May of I Ma		ARANCES	Railing-Railing Part Ty Right Left Ty Rail		4.	Bypass De- four Lengt	ATAC SAA 10	23(1)16	IBVA 2A		X	Leakage Leakage Drainage Profile Profile Filev Lighting Lighting Lighting Lighting Lighting Lighting Lighting		L	Overall Rating Overall Rating Overall Str. Rating Overall Str. Rat		Sth 1 ATECT	9 Sed			
	Latitude			Span Length Section Struct. Code Code		S	HORIZON Curb Shoulder Left	CROSSING DATA	Casting DATA	Feature Crossed		Project Number Constructed	-		DECK	Curb Side- Walks Bridge Raii Fixed Joints Loints		CSERVICES	Clear Sign Bar / Gates Legi- bility Visi- bility Visi- bility		S 4th t ATEST	+			
	Free Foll-Free			Struct. Code I	+	-	Design Curb Strated Shoulder			Function Code Railroad Code	SES	79 19	M95		SPANS	Control Panel Signal Devices Rating		TRAFFIC	Haz, Mark, Słg, Warn, Dev,		T   3rd LATEST	Type Date	RKS		
LOCATION	Place Class  State  Maint, By  Maint, By		אטוואוויים שהואם	<u> </u>		àĹ	batsoq Descod batsoq baaq2 baaq2 LimiJ			Elev. Ft-In Type Kind of Crossing	FNCBOACHMENTS	79 79	VVa Pov	ION DATA	MOVABLE	Wedges  Mach.  Greasing  Elect,	-		Adeq. Overall Rating Speed Lim. Sig		2nd LATES	alect	REMARKS	rict nt. By	nis Tis
LOCA	State City Number Nat. Geog. City Code		a CNCCAS			3	Operating Rating Inventory Rating			Ref. Vert. Clear, Fr. Ref.		A T T	Pet	INSPECTION		Clean. Utilities Overall		ATERWAY	Scour Chae. Chae. Vegeta- tion Drift		R. LATEST	əfaG	MISC.	viron. nd. tional	sse our voc
ļ	District		FXTDA	sned?			X Spans		RSTRUCTURE	Channel Vide (	QUANTITIES	formed Structural	-			Weids Colf. Dam. Deflect.	DATA	WA	Rap Spur Spur Emb. Emb.		REPLACE, PR.	13js12jQ	STRUCTURE	ture ber	_
	Federal Route Mumber	-	FIRST	Section Struct.			Struct. Code No. of Struct.		UNDER	HORIZONTAL Right Left	OG	Concrete			STRUCTURE	Upper Paint	INSPECTION		Em- bank. Overall Rating Revet-		P	Adj. Type Ad Type Ad Improve Propose Improve Improve	NO, ON ST	Structure	
-	State Route Number			gtn No. of lax. Spans		SOLUTION OF THE PARTY OF THE PA	Length			Vertical Ft-In		nage Area			SUPERS	Sway Pracing Verti- Cals nosis		APPROACH	Cuave- rail Align- ment Ret. Wali	ROVEMENTS	,	Est. Design A.D.T. Year o		Cost	raint cop
DEFENSE	epost Section Section		-	Total Length of Max. Span		FIGURE	Section Struct. Code Code	CLEARANCES		Min. Width Width Width Width Width Ft-lin		EY Drainage	вя 			Girders String- ers Dia- phrams Lat. Bracing			Const. Joint Pave- ment Rel. Joint Joint Siab	OSEDIMP	, A	Roadwa Width No. of Lanes		to tol- fini fini si of	Pal Co
DI COLO	Bridge Lefter		-	Section	EXTRA DESCRIPTION	SEVENTH EXTED	No. OV.	CLEAR	VERTICAL	Right Curb Left C Ft-in Ft-in	HYDRAULIC DATA	Micro- Date of			Ş	Bearings Lower Chord Floor Beams			Collision Dam. Paint Clean- liness Overall Rating	PROP	-	men: Design	PAINT	aning finod antity Paint guired	su O
	Major Major Mumber Mumber Section	DESCRIPTION	DRAW SPAN	Oper- froing froing froing fection Operating froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing froing	EXTRA	SEVEN	Section		Z	Centerline Ft-In	HYDR	erial erial liet ucture	PM PM 15			l Inventory		Г	Sett. Crack/ Spalls Steel Corr. Timber Decay			Type  Type  Mork	-	Painted By	
	Bridge I.D Str. Count			Floor Riding Surf. Surf. Thick	+	SIXTH EXTRA	Vo. of Spans Max. Spans		MEDIAN	opinone Shiuone MibiW aqvT		10th's terway terway orm. ream ream	N CI M	NS DATA		Completion struction		3STRUCTUR	Ped- slates Foot- seni Found Polles Piles	SAL	6illy	Materw Materw Appro. Rdwy. P			
	noitos2		MATERIAL	Piers Abut, Piles Piles Founda-			Section			utourts Midiw width seM ts	SS	& o Skew hwater tk Fron evence vation vation	PW IH	PLANS	YAE?	Where Control			Bent Piles Bents Piers Piers	APPRAISAL	000 60.	Struct, C	-	Date Paint Job Was Comp.	s
	Number Number	1		Structu Code Phy. Vr Sub. Struct.		FIFTH EXTRA	Struct. Code No. of Spans		SIDEWALKS	Side of Str.	GEOMETRICS	Degree of Curve				Structure X \$100		<u> </u>	Caps Bulk- Wall Wing-	GDRAIL		Rec Da of Vext Inspecti Type		Project Number For Paint Job	

# APPENDIX F BRIDGE NUMBERING SYSTEM

CONTROL SECTION

CONTROL SECTION LOG MILE

1

NO. OF STRUCTURES AT SAME LOG MILE

EXAMPLES;

1.50 (1)


C. S. 21 - 3 STR. AT LOG 1.50

(1)STR. NO. 021 03 0150 1

0.00 Begin Control

C. S. 1 03 STR. AT LOG 0 - 40 STR. NO. 001 03 0040 1


2



C. S. 450 - 1 STRS. AT LOG 11.55 IN DIRECTION OF INV.

(1)STR. NO. 450 01 1155 1 (2)STR. NO. 450 01 1155 2

0.00 Begin Control



3

C. S. 450-33 WITH FRONTAGE ROADS.

STRS. AT LOG 1.75 IN DIRECTION OF INV.


(1)STR. NO. 450 33 0175 1

(2) STR. NO. 450 33 0175 2

(3)STR. NO. 450 33 0175 3 (4)STR. NO. 450 33 0175 4

0.00 Begin Control

(Con't)




C. S. 7 - 9 WITH STR.
OPPOSITE LANE OF
DIRECTION OF INV. AT LOG
5.80

STR. NO. 007 09 0580 2

0.00 Begin Control



4




C. S. 452-01 WITH FRONTAGE ROADS. STRUCTURES ON FRONTAGE

ROADS ONLY.

(1)STR. NO. 452 01 0225 3 (2)STR. NO. 452 01 0225 4

0.00



6

C. S. 29 - 30 WITH FRONTAGE ROAD.

STRUCTURE ON LEFT FRONTAGE ROAD ONLY.

(1)STR. NO. 029 30 0133 4

0.00

